

Gigabit Interface Converter

High Performance Singlemode Transceiver

DGS-708



D-Link's new line of Gigabit Interface Converters (GBICs) and Small Form-Factor Pluggables (SFPs) transceivers represent an industry leading combination of performance and affordability. D-Link's new Gigabit transceivers are available in two form-factors: standard (GBIC) or (SFP)/mini-GBIC.

The DGS-708 is a high performance 1550nm singlemode GBIC transceiver. Supporting full duplex, Gigabit speeds for a distance of up to 80km on 9µm singlemode fiber. The unit features a metal housing to reduce EMI and to increase durability. The DGS-708 is hot pluggable and is backed by a standard 3-year product warranty and free technical support.

FEATURES

Product Highlights:

- 1550nm Singlemode Transceiver
- Hot Pluggable
- Multi-Vendor¹/Device Support¹
- Metal Enclosure Reduces EMI
- Standards Compliant
- 5.0V Power Supply
- Duplex SC Connector

Performance:

- Up to 80km on 9/125µm
- Up To 1.25Gbps Bi-Directional (Gigabit)
- Up To 1.0625Gbps Bi-Directional (Fiber Channel)

Support Information:

- Free Technical Support
- 3 Year Warranty
- Extended Support Options Available

¹ Third-Party Devices Must Comply With specified Supported Industry-Standard Specifications

D-Link Gigabit Transceivers




PRODUCT	TYPE	VOLTAGE	CONNECTOR	CAT5 UTP	62.5µ Multimode	50.0µ Multimode	9µ Singlemode
DGS-701 (1000BASE-SX GBIC, 3.3V, 220/550m)	GBIC	3.3V	SC	-	220m	550m	-
DGS-702 (1000BASE-LX GBIC, 3.3V Up to 10km)	GBIC	3.3V	SC	-	550m	550m	10km
DGS-703 (1000BASE-LX GBIC, 3.3/5.0V, Up to 10km)	GBIC	3.3V/5.0V	SC	-	550m	550m	10km
DGS-704 (1000BASE-LX GBIC, 3.3V, Up to 30km)	GBIC	3.3V	SC	-	-	-	30km
DGS-705 (1000BASE-LX GBIC, 5.0V, Up to 10km)	GBIC	5.0V	SC	-	-	-	10km
DGS-706 (1000BASE-LX GBIC, 5.0V, Up to 30km)	GBIC	5.0V	SC	-	-	-	30km
DGS-707 (1000BASE-SX GBIC, 3.3V, 220/550m)	GBIC	3.3V	SC	-	220m	550m	-
DGS-708 (1000BASE-LX GBIC, 3.3/5.0V, 80km)	GBIC	3.3V/5.0V	SC	-	-	-	80km
DGS-711 (1000BASE-T GBIC, 3.3V Up to 100m)	GBIC	3.3V	RJ45	100m	-	-	-
DEM-310GM2* (1000BASE-SX+ GBIC, 3.3V Up To 2km)	GBIC	3.3V	SC	-	Up to 2km*	Up to 2km*	-
DEM-310GT (1000BASE-SX SFP, 3.3V, Up to 10km)	SFP	3.3V	LC	-	550m	550m	10km
DEM-311GT (1000BASE-SX SFP, 3.3V, Up to 220/550m)	SFP	3.3V	LC	-	220m	550m	-
DEM-312GT2* (1000BASE-SX+ SFP, 3.3V, Up to 2km)	SFP	3.3V	LC	-	Up to 2km*	Up to 2km*	-
DEM-314GT (1000BASE-LX SFP, 3.3V, Up to 50km)	SFP	3.3V	LC	-	-	-	50km
DEM-315GT (1000BASE-LX SFP, 3.3V, Up to 80km)	SFP	3.3V	LC	-	-	-	80km

* Must be paired with another DEM-310GM2 and/or DEM-312GT2, not for use with other SX GBICs

DGS-708

Gigabit Interface Converter
High Performance 1550nm Singlemode Transceiver

DGS-708



D-Link Gigabit Compatibility Matrix

D-Link MODULE	PRODUCT REV	DGS-1024T	DGS-1024TG	DGS-3224TG	DGS-3224TGR	DGS-3308TG/FG
		A1/B1	B1	A1	A1	B1
DGS-701 (1000BASE-SX GBIC, 3.3V, 220/550m)	A1		✓	✓		✓
DGS-702 (1000BASE-LX GBIC, 3.3V, Up to 10km)	A1		✓	✓		✓
DGS-703 (1000BASE-LX GBIC, 3.3/5V, Up to 10km)	A1		✓	✓		✓
DGS-704 (1000BASE-LX GBIC, 3.3V, Up to 30km)	A1		✓	✓		✓
DGS-705 (1000BASE-LX GBIC, 5.0V, Up to 10km)	A1		✓	✓		✓
DGS-706 (1000BASE-LX GBIC, 5.0V, Up To 30km)	A1		✓	✓		✓
DGS-707 (1000BASE-SX GBIC, 3.3V, 220/550m)	A1		✓	✓		✓
DGS-708 (1000BASE-LX GBIC, 3.3/5.0V, 80km)	A1		✓	✓		✓
DGS-711 (1000BASE-T GBIC, 3.3V, Up to 100m)	A1		✓	✓		✓
DEM-310GM2* (1000BASE-SX+ GBIC, 3.3V, Up To 2km)	A1		✓	✓		✓
DEM-310GT (1000BASE-LX SFP, 3.3V, Up to 10km)	A1	✓			✓	
DEM-311GT (1000BASE-SX SFP, 3.3V, 220/550m)	A1	✓			✓	
DEM-312GT2* (1000BASE-SX+ SFP, 3.3V, Up to 2km)	A1	✓			✓	
DEM-314GT (1000BASE-LX SFP, 3.3V, Up to 50km)	A1	✓			✓	
DEM-315GT (1000BASE-LX SFP, 3.3V, Up to 80km)	A1	✓			✓	

* Must be paired with another DEM-310GM2 and/or DEM-312GT2, not for use with other SX GBICs

Technical Specifications

Product/Performance Specifications

Data Rate Gigabit 1.250Gbps (Bi-Directional)
Data Rate Fiber Channel 1.062Gbps (Bi-Directional)

Optical Receiver Sensitivity -23dBm (Max)

Transmission Range

62.5/125µm N/A
50.0/125µm N/A
9/125µm Up to 80km

Interface Options

Connector Type SC Type

Standards

IEEE 802.3

Operational Ranges

Supply Voltage 3.1-3.5V
Max Voltage 6.0V
Max Current 300mA

Physical Specifications

Dimensions (WxDxH) 1.19x0.47x2.25 in

Safety Certifications and Environmental Information

Class 1 Laser - EN 60825-1
FDA 21 1040.10 & 1040.11
Operating Temperature 0° - 70° C
(32° - 158° F)
Storage -40° - 85° C
(-40° - 185° F)
Humidity Operating: 10% to 85%

Warranty and Support Information

Warranty Limited 3 Year Warranty for as long as the original customer/end user owns the product, (excluding power supplies and fans). Power supplies and fans carry a limited 3 year warranty.
Support Free Technical

Ordering Information

DGS-708 1000BASE-LX Singlemode GBIC