



DI-804V

IP Router/Broadband Internet Gateway with 8 IPSec tunnels support and 4 built-in Fast Ethernet switch LAN ports.

Cable/DSL VPN Router With IPSec and 4-port Switch

The DI-804V is a high-performance broadband Internet Gateway Router with secure data transmission designed for branch office communication. Cost-effectively linking a small office to the outside world through the Internet, the DI-804V offers an alternative to the cost-prohibitive point-to-point dedicated connectivity of leased lines. This business-class router provides IPSec security for Virtual Private Network applications, enabling you to extend your branch network to remote networks, such as your corporate office or a trusted supplier, to act as if the two are a single LAN. In addition, the DI-804V also provides cost-saving Internet functions to let you share a single cable/DSL modem and ISP account among your office users, while providing them with physical connections through the built-in LAN switch ports.

Secure Transmission Over the Internet

The DI-804V prevents your confidential data from being accessed and tampered with when traveling along the public Internet to your destinations. Through VPN tunneling protocols, the DI-804V privatizes your communication channels. You can safely exchange mail and data with your head office over the Internet, without fear of observation, modification, or spoofing.

IPSec and Multi-Level VPN Services

With support for up to 8 IPSec tunnels, the DI-804V can provide flexible VPN implementation for data confidentiality, integrity and origin authentication to remote sites. Supported data encapsulation, encryption and authentication options include IP ESP, DES, 3DES, MD5 and SHA-1. This enables you to carry out applications such as virtual private networks, including Intranets, Extranets, and remote user access.

Powerful Routing Engine

The DI-804V is equipped with a powerful 32-bit RISC CPU and large RAM to perform its intensive security tasks. This allows the router to run without data throughput degradation while supporting DES/3DES encryption and other security features.

Business-class LAN Security

The DI-804V provides firewall security using Stateful Packet Inspection (SPI) and hacker attack logging for Denial of Service (DoS) attack protection, plus VPN pass-through for extra security. SPI inspects the contents of all incoming packet headers before deciding what packets are allowed to pass through. The DI-804V also blocks and re-directs certain ports to limit the services that outside users can access on your network. Virtual Server Mapping is used to re-task services to multiple servers. The DI-804V can be set to allow separate FTP, Web, and Multiplayer game servers to share the same Internet-visible IP address

while still protecting your servers and workstations from hackers. To monitor hacker attacks, the DI-804V can log up to 32 event messages showing possible attacks.

DMZ Host to Open Public Domain

A DMZ setting can be applied to a single client (such as a Web server) behind the DI-804V to fully expose it to the Internet and ensure complete Internet application compatibility even if the specific port is not known. This allows you to set up web sites and e-commerce applications from your office while maintaining protection for the rest of your office LAN.

Simplified, Cost-saving Broadband Internet Connection

Of course, the basic benefit is to share the broadband line to the entire office, using a single cable or DSL modem. To let everybody logon, the DI-804V automatically creates and assigns an IP number for each computer, simplifying every one's logon operation.

4 Switch Ports for Ready LAN Connection

With 4 built-in auto-sensing 10/100Mbps Fast Ethernet switch ports, the DI-804V provides ready connection for workstations and servers, saving you the cost and trouble of installing a separate LAN switch.

UPnP Enabled for Compatibility

The DI-804V is designed for easy and robust connectivity among heterogeneous standards-based network devices. Computers can communicate directly with the DI-804V for automatic opening and closing of UDP/TCP ports to take full advantage of security provided without sacrificing functionality of on-line applications such as video conferencing.

Features

- Broadband Internet Gateway (NAT router)/IP router with VPN
- 168-bit 3DES IPSec advanced VPN security
- 3DES with SHA-1 advanced secure configuration
- Up to 8 VPN tunnels to 8 remote sites
- Packet filtering firewall protection
- Broadband DSL or cable modem connection
- ISDN or 56Kbps analog modem backup
- Dial-on-Demand & idle timer auto-disconnection (for dial-up)
- ISDN & analog connection
- Virtual servers & DMZ support
- Web-based configuration setup
- Firmware upgradeable with future enhanced versions
- Universal Plug-n-Play (UPnP) enabled

Hardware

Number of Ports

- 1 RJ-45 10BASE-T port for DSL/Cable modem connection
- 1 DB-9 RS-232 port (460Kbps Baud) for ISDN TA/analog modem connection (for WAN backup)
- 4 RJ-45 10BASE-T/100BASE-TX 10/100Mbps LAN switch ports

CPU

Arm7 32-bit RISC

Memory

- SDRAM: 16MB
- Flash: 1MB

Factory Reset

1 push button

WAN

Number of WAN Ports

- 1 RJ-45 10BASE-T port for DSL/Cable modem connection
- 1 DB-9 RS-232 port (460Kbps Baud) for ISDN TA/analog modem connection (for WAN backup)

Broadband Support

- ADSL modem
- Cable modem
- PPP over Ethernet

Backup Link Support

- Dial-up ISDN TA
- Dial-up Analog modem
- PPP
- Dial-on-Demand with auto login to ISP
- Auto-disconnect with user-defined idle timer
- PAP/CHAP security

Routing

Routed Packet Type

IP packets

Routing Protocols & Methods

- RIP-1, RIP-2

Static Routing

- Dynamic Routing

Firewall Security

Stateful Packet Inspection (SPI) to prevent Denial of Service(DoS) attacks (Syn flood, ICMP flood, UDP flood, "ping of death", IP spoofing, land attack, tear drop attack, IP address sweep attack, Win Nuke attack), Intrusion Detection Logging and LAN/WAN filtering.

VPN

Functionality

Eight (8) dedicated VPN tunnels, Manual key and IKE Security Association(SA) assignment, 56-bit (DES) or 168-bit (3DES) IPSec encryption algorithm, MD5 or SHA-1 authentication algorithm, pre-shared key, perfect forward secrecy (Diffie-Helman AND Oakley client support), key life and IKE lifetime settings, prevent replay attack, remote access VPN (client-to-site), site-to-site VPN, VPN pass-through.

VPN Layers

- Layer 2 pass-through
- Layer 3 with IPSec

VPN Layer 2 Protocols

- PPTP (Point-to-Point Tunneling Protocol)
- L2TP

Application Support

- IPSec pass-through
- PPTP
- NetMeeting

Layer 3 IPSec Security

Data Encryption Methods

- IP ESP (Encapsulating Security Payload)
 - Confidentiality over IP payload
 - Optional authentication of IP payload and ESP header
- Null encryption

Encryption Transforms

- DES (Data Encryption Standard)
- 3DES

Authentication Transforms (for ESP and AH)

- MD5
- SHA-1

Supported Key Management Protocol

Internet Security Association and Key Management Protocol (ISAKMP)

Connection Modes

- Site to Site
- Client to Site

Number of Tunnels

8 IPSec tunnels (max.)

Internet Gateway

Supported Functions

- Network Address Translation (NAT)
- DHCP server automatic IP assignment
- Virtual server

Packet Inspection

Stateful Packet Inspection (SPI)

Hacker Attack Logging 32 event messages (max.)

RFC Support

- PPTP client and server (RFC 2637)
- IPSec tunnel mode (RFC 2401)
- HMAC-MD5-96 (RFC 2403)
- HMAC-SHA1-96 (RFC 2404)
- Encapsulation Security Payload Protocol (RFC 2406)
- DHCP server (RFC 2131)
- DHCP client (RFC 2131)
- IP routing (RIP1, RIP2) (RFC 2453)
- NAT (many-to-one) (RFC 1631)
- IP control Protocol (RFC 1332)
- PPPoE (RFC 2516)

LAN

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation
- IEEE 802.3x full-duplex flow control

LAN Protocol CSMA/CD

Topology

Star

Number of LAN Ports

4 RJ-45 10BASE-T/100BASE-TX auto-sensing switch ports

Data Transfer Rates

- Ethernet:
 - 10Mbps (half duplex)
 - 20Mbps (full duplex)
- Fast Ethernet:
 - 100Mbps (half duplex)
 - 200Mbps (full duplex)

Network Cables

- 10BASE-T:
 - UTP Cat. 3, 4, 5 (100 m max.)
 - EIA/TIA-586 100-ohm STP (100 m max.)
- 100BASE-TX:
 - UTP Cat. 5 (100 m max.)
 - EIA/TIA-568 100-ohm STP (100m max.)

Media Interface Exchange

MDI-II/MDI-X auto-sensing for all LAN ports

Packet Switching Method

Store-and-forward

MAC Address Filtering Table

1K entries per device

MAC Address Learning

Automatic update

Management & Configuration

IP Number Self-identification

Through DHCP client

Local & Remote Management

Web-based utilities (via browser)

Firmware Upgrade

Web-based (via browser)

Physical & Environmental**Diagnostic LEDs**

- Link (WAN port and serial port)
- Act (WAN port and serial port)
- Link/Act (per LAN port)
- 100Mbps (per LAN port)
- Power (per device)

Power Supply

- DC 5V 1.5A
- Through external AC power adapter

Dimensions

190 x 117 x 31 mm palm-sized

Weight

360 grams (approx.)

Operating Temperature

-5° - 45°C (23° - 113°F)

Storage Temperature

-20° - 70°C (-4° - 158°F)

EMI Certification

- FCC Class B
- CE Class B
- C-Tick Class B
- BSMI Class B



ACN 052 202 838

Ordering Information**Broadband Internet Gateway With VPN Security**

- DI-804V** 1 RJ-45 10BASE-T port (for ADSL/cable modem connection)
1 RS-232 COM port (for ISDN TA/analog modem connection)
4 RJ-45 10BASE-T/100BASE-TX switch ports

Please specify one of the following after the model number:

- /U Includes no AC power adapter
- /A Includes an American standard AC power adapter
- /E Includes an EU standard AC power adapter
- /B Includes a UK standard AC power adapter
- /N Includes an Australian standard AC power adapter

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-849-788-0905	FAX: 1-849-753-7033	www.dlink.com
Canada	TEL: 1-805-8295033	FAX: 1-905-8295095	www.dlink.ca
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	www.dlink.co.uk
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	www.dlink.co.uk
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	www.dlink.de
France	TEL: 33-1-30238688	FAX: 33-1-30238689	www.dlink-france.fr
Benelux	TEL: 31-40-2688713	FAX: 31-40-2688666	www.dlink-benelux.nl
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	www.dlink.it
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795	www.dlinkiberia.es
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	www.dlink.se
Norway	TEL: 47-22-991890	FAX: 47-22-207039	www.dlink.no
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	www.dlink.dk
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-81661	www.dlink-fi.com
Singapore	TEL: 65-774-6233	FAX: 65-774-6322	www.dlink-intl.com
Australia	TEL: 61-2-94177100	FAX: 61-2-94171077	www.dlink.com.au
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9688	www.dlink.co.jp
China	TEL: 86-10-9809-7777	FAX: 86-10-9809-6789	www.dlink.cn
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914	www.dlink-india.com
Middle East	TEL: 202-6356176	FAX: 202-6356192	www.dlink-me.com
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923	www.dlink.cl
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186	www.d-link.co.za
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390	www.dlink.ru
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515	www.dlinktw.com.tw
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299	www.dlink.com.tw



RECYCLABLE

Rev. 01 (June 2002)

Printed in Taiwan

