



### AirPlus G+



DWL-G520+



## 802.11g Wireless LAN PCI Card

### Real Throughput Up to 10X Faster

The D-Link AirPlusG+™ DWL-G520+ wireless PCI card is an enhanced 802.11g high-performance, wireless card for desktop computers. This card supports high-speed wireless networking of up to 54Mbps, while providing seamless interoperability with all existing 802.11b and 802.11b+ wireless equipment. Together with better security, this card is the ideal wireless solution that offers an upgrade to a fast, new technology while protecting your past investments through interoperability with your current network equipment.

#### Up to 54Mbps Transmission Speed

The DWL-G520+ provides speeds of up to 54Mbps when used with other D-Link AirPlusG+™ and other 802.11g products. This compares favorably with 802.11b adapters that offer 11Mbps speed, and with 802.11b+ adapters that give 22Mbps transmission.

This enhanced speed and adoption of 2.4GHz frequency, now available for public use in most countries, plus the mobility and convenience inherent in a wireless LAN, make this card an ideal solution for bandwidth intensive WLAN applications.

#### Real Throughput 10 Times Faster Than 802.11b Wireless Adapters

Apart from the higher theoretical network data transfer speed of 54Mbps for 802.11g against the 11Mbps for 802.11b, the DWL-G520+ also delivers a much faster data transmission than other wireless LAN adapters. In a typical working environment with multiple users accessing the network at the same time, the DWL-G520+ operates at 10 times the speed of a normal 802.11b wireless LAN adapter, which is made possible by means of a turbo engine driver supplied with this card.

#### Compatible With 802.11b and 802.11b+

Like the 802.11b and 802.11b+ adapters, the DWL-G520+ uses a single 2.4GHz wireless frequency, eliminating the

complexity of dualband networking. 802.11g's compatibility with existing wireless LAN standards means that you do not need to change your entire network to maintain connectivity.

#### Easy Migration to Higher Bandwidth

By maintaining compatibility with your existing wireless network equipment, this adapter lets you upgrade to a higher speed at the pace you want. The DWL-G520+ and other 802.11g standard devices can be gradually added to your network, while the rest of your older network remains perfectly connected.

#### Advanced Security

In addition to offering faster data transfer speeds, this card also provides the newest, strongest, most advanced security features available today. For home users that do not incorporate a radius server in their networks, security is provided in a convenient, automatic way (when used in conjunction with other 802.11g products). No longer will you have to frequently input a new WEP key to execute security operations. With the DWL-G520+, you will automatically receive a new key every time you connect, doing away with the inconvenience of manual WEP key input. The DWL-G520+ provides a stronger network security with 64, 128 and 256-bit WEP data encryption.

### Key Features

- 802.11g wireless LAN standard
- Up to 54Mbps data transfer rate \*
- Real throughput 10x faster than 802.11b \*\*
- Backward compatible with 802.11b/11b+ standard
- Dynamic data rate scaling at 1, 2, 5.5, 6, 9, 11, 12, 18, 22, 24, 36, 48 and 54Mbps
- Maximum reliability, throughput and connectivity with automatic data rate switching
- Utilizes OFDM (Orthogonal Frequency Division Multiplexing) technology
- Strong network security with 64/128/256-bit WEP data encryption
- 32-bit PCI bus high performance
- User-friendly configuration and diagnostic utility.
- Connects up to 100 meters indoors, 400 meters outdoors \*\*\*

\* When used with other 802.11g devices

\*\* When used with AirPlusG+™ products

\*\*\* Environmental factors may adversely affect range

# DWL-G520+

## Technical Specifications

## 2.4GHz Wireless LAN

### Hardware

#### System Requirements

- Computer with available PCI extension bus slot
- Windows XP, 2000, ME or 98 SE
- 300MHz CPU or above
- 32MB memory or more

#### Wireless LAN Standards

- 802.11b
- 802.11b+
- 802.11g

#### PCI Bus Standard

PCI 2.2

#### Data Rates

- 802.11g: up to 54Mbps (6/9/12/18/24/36/48/54Mbps)
- 802.11b+: up to 22Mbps
- 802.11b: up to 11Mbps (1/2/5.5/11Mbps)

#### Transmission Technology

DSSS

#### RF Frequency Range

2.4 to 2.4835GHz

#### Frequency Stability

Within +/- 25ppm

#### Operating Channels

- 1 to 11 channels (North America)
- 1 to 13 channels (Europe)

#### Data Modulation Type

DBPSK, DQPSK, CCK, PBCC and OFDM (BPSK/QPSK/16-QAM/64-QAM)

#### Antenna

2dBi Gain detachable external antenna (reverse SMA connector)

#### Transmit Output Power

- 802.11b: 16dBm (typical)
- 802.11g: 14dBm (typical)

#### Receive Sensitivity (for 802.11b)

(typically @PER < 8% packet size 1024 @ 25 °C +/- 5 °C)

- 22Mbps (PBCC): -80dBm
- 11Mbps (PBCC): -85dBm
- 11Mbps (CCK): -84 dBm
- 5.5Mbps (CCK): -87 dBm
- 2Mbps (QPSK): -90 dBm
- 1Mbps (BPSK): -92 dBm

#### Receive Sensitivity (for 802.11g)

(typically @PER < 8% packet size 1024 @ 25 °C +/- 5 °C)

- 54Mbps (OFDM): -71 dBm
- 48Mbps (OFDM): -72 dBm
- 36Mbps (OFDM): -77 dBm
- 24Mbps (OFDM): -80 dBm
- 12Mbps (OFDM): -86 dBm
- 9Mbps (OFDM): -87 dBm
- 6Mbps (OFDM): -89 dBm

#### Operating Range \*

- Indoors: 100 meters (328 feet)
- Outdoors: 400 meters (1,312 feet)

\* Environmental factors may adversely affect range

#### Diagnostic LED

Wireless Link/Act

### Software Features

#### Network

- Auto-switch to select 802.11g or 802.11b mode
- Supports Ad-Hoc, Infrastructure WLAN network
- Wireless roaming
- Site rate auto fall-back under noisy environment or longer range distance
- Data Survey with Profile function

#### Security

- WEP 64/128/256-bit data encryption (user-selectable)
- 802.1x security (MD5 and TLS) (in Windows XP only)
- Wi-Fi™ Protected Access

### Configuration & Management

- Plug-and-Play setup and installation
- Management Utility supports Windows 98SE, ME, 2000, XP

### Physical & Environmental

#### Power Supply

3.3 VDC +/- 5%

#### Power Consumption (802.11g)

- Transmit: 650mA
- Receive: 450mA
- Stand-by: 20mA

#### Power Consumption (802.11b)

- Transmit: 500mA
- Receive: 450mA
- Stand-by: 20mA

#### Dimensions

134 x 121 x 22 mm

#### Weight

92 grams

#### Operating Temperature

0° to 55 °C

#### Storage Temperature

-20° to 65 °C

#### Humidity

5% to 95% non-condensing

#### Regulation Compliance

- US: FCC Part 15 Class B
- Europe: CE/R&TTE

#### Box Includes

- DWL-G520+ wireless PCI card
- CD (includes drivers, user's manual, Quick Installation Guide, Acrobat Reader 5.0)
- Quick Installation Guide (printed)



## Ordering Information

DWL-G520+

802.11g wireless LAN PCI card

Please specify your model number as follows:

DWL-G520+/NA  
DWL-G520+/EU  
DWL-G520+/CN  
TDWL-G520+

North America frequency  
EU frequency  
For use in China (China packaging)  
For use in Taiwan (Taiwan packaging)

# D-Link®

Specifications subject to change without prior notice.  
D-Link is a registered trademark and AirPlusG+ is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

#### U.S.A

#### Canada

#### Europe

#### Germany

#### France

#### Netherlands

#### Belgium

#### Italy

#### Iberia

#### Sweden

#### Norway

#### Denmark

#### Finland

#### Singapore

#### Australia

#### Japan

#### China

#### India

#### Middle East (Dubai)

#### Turkey

#### Egypt

#### Israel

#### Latinamerica

#### Brasil

#### South Africa

#### Russia

#### Taiwan

#### D-Link Corp.

TEL: 1-714-885-6000

TEL: 1-905-8295033

TEL: 44-20-8731-5555

TEL: 49-6196-77990

TEL: 33-1-30238688

TEL: 31-10-282-1445

TEL: 32(0)2-517-7111

TEL: 39-2-2900-0676

TEL: 34-93-4090770

TEL: 46-(0)8564-61900

TEL: 47-22-309075

TEL: 45-43-969040

TEL: 358-9-2707-5080

TEL: 65-6774-6233

TEL: 61-2-8899-1800

TEL: 81-3-5434-9678

TEL: 86-10-8518-2533

TEL: 91-022-652-6696

TEL: 971-4-8834234

TEL: 90-212-335-2553

TEL: 202-414-4295

TEL: 972-9-9715700

TEL: 56-2-232-3185

TEL: 55-11-55039320

TEL: 27(0)1266-52165

TEL: 7-095-744-0099

TEL: 886-2-2910-2626

TEL: 886-2-2916-1600

FAX: 1-866-743-4905

FAX: 1-905-8295223

FAX: 44-20-8731-5511

FAX: 49-6196-7799300

FAX: 33-1-30238689

FAX: 31-10-282-1331

FAX: 32(0)2-517-6500

FAX: 39-2-2900-1723

FAX: 34-93-4910795

FAX: 46-(0)8564-61901

FAX: 47-22-309085

FAX: 45-43-424347

FAX: 358-9-2707-5081

FAX: 65-6774-6322

FAX: 61-2-8899-1868

FAX: 81-3-5434-9868

FAX: 86-10-8518-2250

FAX: 91-022-652-8914

FAX: 971-4-8834394

FAX: 90-212-335-2500

FAX: 202-415-6704

FAX: 972-9-9715601

FAX: 56-2-232-0923

FAX: 55-11-55039321

FAX: 27(0)1266-52186

FAX: 7-095-744-0099#350

FAX: 886-2-2910-1515

FAX: 886-2-2914-6299



RECYCLABLE

Rev. 03 (Jun. 2004)