

# 10-Gigabit CX4 Module

## 10-Gigabit Connection on Coaxial Cable

- 1 or 2 10Gigabit CX4 Ports
- Up to 20Gbps Full Duplex Per Port
- IEEE 802.3ak Standard Compliance
- Cost-Effective Twin-Axial Copper Cable

### FEATURES

- **20-Gigabit Performance (Full Duplex Operation) Per Port**
- **Complies With IEEE 802.3ak Standard**
- **Supports Twin-Axial Copper Cable Lengths Up to 15 m to 20 m**
- **Cost-Effective, Very High-Speed Connection With Low Latency**
- **No External Transceivers Required**
- **1-m Copper Cable Provided**
- **Optional Copper Cables of Longer Lengths Available**

The D-Link CX4 port module provides enterprises with a highly affordable, low-latency 10-Gigabit network connection on the twin-axial copper cable. Significantly lower in cost than the fiber cable, this copper cable supports distances ranging up to 15 to 20 meters, depending on wire gauge. The CX4 port module does not require any transceiver to be installed, eliminating the need for costly fiber transceivers.

The CX4 port module slides into an open slot of a D-Link Gigabit switch. The port provides a very high bandwidth of 20-Gigabit operating in the full duplex mode. It can be used to stack the switches together in a very high bandwidth stacking scheme, or to uplink them to core chassis switches. It can also be deployed to connect to servers or network storage devices with CX4 support.

The CX4 port module is thus an ideal solution for high-bandwidth network connections in high-performance computing clusters and for short distances within wiring closets.



**DEM-410CX Module**

- 1 CX4 Port
- Compatible With DGS-3400 Series Gigabit Switches



**DEM-420CX Module**

- 2 CX4 Ports
- Compatible With DXS-3300 Series Gigabit Switches



**DEM-CB300CX Optional Twin-Axial Copper Cable**

- 3 Meters' Length

## Technical Specifications

### Operation

Full-duplex (20Gbps)

### Diagnostic LEDs

Link/Activity

### Dimensions

- DEM-410CX: 150mm x 57mm x 28mm (L xW xH)
- DEM-420CX: 175mm x 130mm x 27mm (L xW xH)

### Weight

- DEM-410CX: 166 grams
- DEM-420CX: 375 grams

### Operating Temperature

0° to 40°C

### Storage Temperature

-10° to 70°C

### Operating Humidity

10% to 90% RH non-condensing

### Storage Humidity

5% to 90% RH non-condensing

### Emission

- FCC Class A
- CE
- C-Tick



## D-Link Worldwide Offices

<b>U.S.A.</b>	TEL: 1-800-326-1688	FAX: 1-866-743-4905	<b>Luxemburg</b>	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295223	<b>Poland</b>	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
<b>Europe (U. K.)</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	<b>Hungary</b>	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300	<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689	<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Netherlands</b>	TEL: 31-10-282-1445	FAX: 31-10-282-1331	<b>India</b>	TEL: 91-022-26526696	FAX: 91-022-26528914
<b>Belgium</b>	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	<b>Middle East (Dubai)</b>	TEL: 971-4-3916480	FAX: 971-4-3908881
<b>Italy</b>	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	<b>Turkey</b>	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	<b>Egypt</b>	TEL: 202-414-4295	FAX: 202-415-6704
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347	<b>Israel</b>	TEL: 972-9-9715700	FAX: 972-9-9715601
<b>Norway</b>	TEL: 47-99-300-100	FAX: 47-22-309580	<b>LatinAmerica</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Finland</b>	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	<b>Brazil</b>	TEL: 55-11-218-59300	FAX: 55-11-218-59322
<b>Spain</b>	TEL: 34-93-4090770	FAX: 34-93-4910795	<b>South Africa</b>	TEL: 27-12-665-2165	FAX: 27-12-665-2186
<b>Portugal</b>	TEL: 351-21-8688493		<b>Russia</b>	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
<b>Czech Republic</b>	TEL: 420-(603)-276-589		<b>China</b>	TEL: 86-10-58635800	FAX: 86-10-58635799
<b>Switzerland</b>	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	<b>Taiwan</b>	TEL: 886-2-6600-0123	FAX: 886-2-6600-8168
<b>Greece</b>	TEL: 30-210-9914 512	FAX: 30-210-9916902	<b>Headquarters</b>	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898