



DI-524

802.11g Wireless Broadband Router

With Built-in 4-Port Switch

The D-Link AirPlusG DI-524 wireless router is the ideal networking solution for homes and small offices. This router combines the high-speed 802.11g wireless technology and robust firewall security features in providing broadband Internet connection to a small workgroup. It's an ideal device for those creating their first wireless networks, as well as for more advanced users looking for advanced network protection and content filtering.

High-Speed Wireless Speed

The DI-524 router offers a maximum wireless signal rate of up to 54Mbps through its wireless channels, allowing streaming videos and other high bandwidth applications such as on-line gaming and video clips to operate without the hassle of Ethernet cables. The ability to handle high bandwidth applications also makes streaming real time programs more enjoyable and more efficient.

Advanced Built-in Firewall

The DI-524's built-in firewall makes it more difficult for hackers to penetrate your network. Firewall features include functions to allow or disallow certain ports to be open for certain applications. Time scheduling can be applied to the firewall rules to have specific ports open at certain times and to be closed at other times. Features like content filtering, MAC filtering, URL blocking, and domain blocking are useful tools to prevent unwanted intruders from connecting to your network or browsing restricted sites.

Easy Setup and Secure Data Transfer

A simple, intelligent web-based setup wizard is provided with the DI-524 to allow users to quickly set up the router and connect computers to share a high-speed Internet connection, files, resources, games or just to communicate. Multiple wireless clients can also securely connect to the network using 64-bit or 128-bit WEP data encryption.

Integrated Ethernet Switch

An integrated 4-port switch allows ready connection of up to 4 computers. This saves you the cost of purchasing and installing a separate switch for network computer connections.

Key Features

- Remote router with 802.11g wireless LAN interface
- Cable/DSL modem Internet sharing
- Wireless LAN speed up to 54Mbps
- 10/100BASE-TX port for DSL/cable modem connection
- WAN port supports PPPoE for Internet dial-up mode
- 4 built-in 10/100BASE-TX switch ports with auto MDI/MDIX support
- Firewall features include NAT with VPN pass-through, MAC/IP/URL filtering, domain blocking and scheduling
- Web-based configuration with setup wizard for quick installation

Standards

- IEEE 802.11g
- IEEE 802.11b
- IEEE 802.3
- IEEE 802.3u

Wireless Modulation Technology

Orthogonal Frequency Division Multiplexing (OFDM)

Wireless Frequency Range

2.4GHz to 2.462GHz

Wireless Signal Rates

(With automatic fallback)

54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps, 5, 5Mbps, 2Mbps, 1Mbps

Wireless Receiver Sensitivity

- 54Mbps OFDM, 10% PER, -68dBm
- 48Mbps OFDM, 10% PER, -68dBm
- 36Mbps OFDM, 10% PER, -75dBm
- 24Mbps OFDM, 10% PER, -79dBm
- 18Mbps OFDM, 10% PER, -82dBm
- 12Mbps OFDM, 10% PER, -84dBm
- 11Mbps CCK, 8% PER, -82dBm
- 9Mbps OFDM, 10% PER, -87dBm
- 6Mbps OFDM, 10% PER, -88dBm
- 5.5Mbps CCK, 8% PER, -85dBm
- 2Mbps QPSK, 8% PER, -86dBm
- 1Mbps BPSK, 8% PER, -89dBm

Wireless Transmit Output Power

15dBm +/- 2dBm

External Antenna Type

Single detachable reverse SMA

Wireless Operating Range

- Indoors: up to 100 m
- Outdoors: up to 300 m

* Environmental factors may adversely affect operating range

Security

- 802.1x user authentication support
- 64-, 128-WEP wireless data encryption
- WPA Wi-Fi Protected Access (WEP with TKIP, MIC, IV Expansion, Shared Key Authentication)

Firewall Features

- NAT (Network Address Translation) with VPN pass-through
- MAC address filtering
- IP address filtering
- URL filtering
- Domain blocking
- Scheduling

VPN Pass-Through/Multi-Sessions

- PPTP
- L2TP
- IPSec

Device Management

- Web-based Internet Explorer v6 or Netscape Navigator v6 or other Java-enabled browsers
- DHCP Server and Client

Diagnostic LEDs

- Power
- Status
- WAN
- LAN (10/100Mbps)
- WLAN

Physical & Environmental**Power Input**

Through external power adapter

Dimensions

273 (L) x 205 (W) x 66 (H) mm

Weight

1.32 kg

Operating Temperature

0° to 40°C

Humidity

90% maximum (non-condensing)

Safety and Emissions

- FCC
- CE
- C-Tick

**Ordering Information**

DI-524 802.11g Wireless Router With Built-in 4-Port Switch

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark and AirPlusG is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Norway	TEL: 47-23-897189	FAX: 47-22-309085
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795
Portugal	TEL: 351-21-8688493	
Czech Republic	TEL: 420-(603)-276-589	
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902
Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
India	TEL: 91-022-26526696	FAX: 91-022-26528914
Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
LatinAmerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
China	TEL: 86-10-58635800	FAX: 86-10-58635799
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
Headquarters	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299