

Product Highlights

Enterprise Class Concurrent Dual Band Wireless Radio
Supports 2x2 MIMO 2.4/5GHz 802.11a/b/g/n with throughput speeds up to 300Mbps.

Flexible Housing Design

Embedded antennas with external antenna option and IP65 water and dust proof housing for an easy deployment in any outdoor application.

Wireless Management Support

Works with DWC-1000 Wireless Controller and DWS-3160/4026 Unified Wireless Switch for larger AP installations that require centralized configuration and management.



DWL-6600AP-O

Unified N Concurrent Dual-band PoE Outdoor Access Point

Features

Ideal for Business

- Blazing wireless performance of up to 300 Mbps¹ network throughput
- Configuration Replicating Clusters reduce configuration complexity
- Up to 32 virtual access points may be created from a single device²
- Automatic load-balancing among neighboring access points
- Flexible QoS with WMM

Trusted Security

- WPA/WPA2 Personal
- WPA/WPA2 Enterprise
- WEP Encryption
- 802.1X User authentication
- MAC address filtering
- Rogue AP detection

Convenient Installation³

- Thanks to its waterproof housing can be easily mounted everywhere
- 802.3af Power Over Ethernet enables installation in installation in hard-to-reach locations
- IP65 certified enclosure

The DWL-6600AP-O Unified N Dual-band PoE Outdoor Access Point is a best-in-class AP designed specifically for business-class environments. With high data transmission rate and Access Point load balancing, the DWL-6600AP-O offers high-quality and reliable WiFi service. Versatile and powerful, the DWL-6600AP-O can be flexibly deployed as a standalone wireless access point or as a managed access point controlled by a D-Link® Unified Wireless Switch or Wireless Controller. Businesses can start with standalone mode deployment, then migrate to a centrally managed system anytime later.

Enhanced Performance

The DWL-6600AP-O delivers reliable wireless performance with maximum wireless signal rates of up to 300 Mbps in either the 2.4 GHz or 5 GHz mode. Support for Wi-Fi Multimedia™ (WMM) Quality of Service features makes the DWL-6600AP-O an ideal access point for audio, video, and voice application. In addition, the load balancing feature ensures maximum performance and best service quality in the wireless environment.

Configuration Replicating Clusters

For small businesses that need to deploy multiple access points (APs) but lack the resources to tackle the complicated task of network management, the DWL-6600AP-O's clustering feature offers the ideal solution. When a small number of DWL-6600AP-O's is deployed on the network, they may be configured to form a cluster. Once the administrator is through with configuring one access point, the same configuration can then be applied to all remaining APs that are members of that cluster. Up to 16 APs may be used to form a cluster.



DWL-6600AP-O

Unified N Concurrent Dual-band PoE Outdoor Access Point

Unified Management

The DWL-6600AP-O can operate in conjunction with a D-Link Wireless Switch or Wireless Controller. In this mode, multiple DWL-6600AP-Os can connect directly or indirectly to one of these switches or controllers to provide more security and wireless mobility for wireless clients. Each DWL-6600AP-O can be managed by these switches to provide the best RF channels and transmission power for all mobile clients, giving them the best wireless signals in both 2.4GHz and 5.0GHz bands and uninterrupted wireless connectivity.

Security

The DWL-6600AP-O supports the latest standards in Wi-Fi security, including WEP, WPA, WPA2, and 802.1X. In addition, the DWL-6600AP-O supports up to 16 virtual AccessPoint (VAP) per radio, for a total of 32 VAPs, which allows the administrator to assign different access privileges to different groups of users. When Station Isolation is enabled, the AP blocks communication between wireless clients on the same radio and VAP. Rogue APs in the network may be easily detected, and the administrator will be immediately notified of any security threat. When used together with D-Link's line of Unified Wireless Switches or Wireless Controllers, the security can be raised to a new level.

Automatic RF Management

When a number of access points are deployed close to each other, interference may result if proper RF management is not implemented. When a DWL-6600AP-O senses any neighbor AP at startup, it will automatically select a non-interfering channel, the DWL-6600AP-O will automatically lower its transmission power to minimize interference. When that managed AP is no longer present, the DWL-6600AP-O will increase its transmit power to expand coverage.

Quality of Service

The DWL-6600AP-O is WMM-certified, so in the event of network congestion, time-sensitive traffic can be given priority ahead of other traffic. Furthermore, when a number of DWL-6600AP-Os are in close proximity with each other, an AccessPoint can refuse new association request once its resources are fully utilized. Instead, the association request will be picked up by a neighboring AP. This feature ensures that no single AP is overburdened while other APs nearby sit idle.

Convenient Installation

With an embedded antenna and IP65 water and dust proof housing, the DWL-6600AP-O can be installed on a wall outside or whenever you need. For easy installation, the DWL-6600AP-O has integrated 802.3af Power over Ethernet (PoE) support, allowing installation of this device in areas where power outlets are not readily available.





DWL-6600AP-O

Unified N Concurrent Dual-band PoE Outdoor Access Point

| Technical Specifications | | |
|---|--|--|
| System | | |
| Wi-Fi Interface | • 802.11a/b/g/n 2.4/5.0 GHz | |
| LAN Interface | • 10/100/1000 Gigabit Ethernet | |
| Console | • RJ-45 | |
| Antenna | • 2x2 MIMO embedded antenna with 4 external antenna connectors | |
| Power Method | • IEEE 802.3af Power Over Ethernet or external power adapter | |
| Wireless Frequency | • 802.11n: 2.4 to 2.497 GHz and 4.9 to 5.85 GHz • 802.11b/g: 2.4 to 2.4835 GHz | • 802.11a: 5.15 to 5.35 GHz and 5.725 to 5.825 GHz |
| Data Transfer Rate | • 802.11n: 6.5 Mbps-130 Mbps (20 MHz) 6.5 MHz-300 Mbps (40 Mbps) | • 802.11a/g: 54, 48, 36, 24, 18, 12, 9, and 6 Mbps • 802.11b: 11, 5.5, 2 and 1 Mbps |
| Operation Channel (2.4 GHz) | • 5.0 GHz: 12 Non-Overlapping Channels for US and Canada | • 2.4 GHz: 11 channels for United States |
| System Management | • HTTP/HTTPS Web-based User Interface | • SNMP, SSH, Telnet Command Line |
| Security | | |
| SSID | • 16 SSID per frequency band, 32 SSID per AP | • Station Isolation |
| Wireless Security | • WEP • Dynamic WEP | • WPA Personal/ Enterprise • WPA2 Personal/ Enterprise |
| Detection & Prevention | • Rogue and Valid AP Classification | |
| Authentication | • MAC Address Filtering | • 802.1x |
| Physical & Environmental | | |
| Power Adapter | • 12 V 1 A | |
| Power over Ethernet | • 48 VDC +/- 10% | |
| Stand-Alone Mode | • WEP/WPA/WPA2 Security • Rogue AP Detection • Station Isolation • MAC Address Filtering • AP Load Balancing Setup | • WDS • AP Clustering • QoS/WMM • Local Storage Configuration |
| Managed Mode (Managed by D-Link Wireless Switch/ Wireless Controller) | • Centralized Management • Centralized Firmware Dispatch • Visualized AP Management Tool • Auto-Power Adjustment • Dynamic Auto-Channel Selection • L2 Fast Roaming • L3 Fast Roaming • Captive Portal • WEP/WPA/WPA2 Security | • Rogue AP Detection • Rogue AP Mitigation • WIDS • Station Isolation • MAC Address Filtering • AP Load Balancing Setup • WDS • QoS/WMM |
| Dimensions | • 240 x 190 x 90 mm | |
| Weight | • 1.76 lbs (0.8kg) | |
| Operating Temperature | • 14°F to 122°F (-10° to 50°) | |

DWL-6600AP-O

Unified N Concurrent Dual-band PoE Outdoor Access Point

| | | | | | |
|-----------------------------|---|-------------------|-----------------|--------------------------|--------|
| Operating Humidity | • 10% to 90% non-condensing | | | | |
| EMI/EMC/RF | • FCC Class B • CE Class B | • C-tick, • IC | • VCCI • NCC | • TELEC • EN60601-1-2 | • IP65 |
| Safety | • cUL | • LVD (EN60950-1) | • UL2043 | | |
| MTBF | • 497,476 hours | | | | |
| Warranty | | | | | |
| Warranty | • Limited Lifetime | | | | |
| Ordering Information | | | | | |
| <i>Part Number</i> | <i>Description</i> | | | | |
| DWL-6600AP-O | Unified N Concurrent Dual-band PoE Outdoor Access Point | | | | |
| Optional products | | | | | |
| <i>Part Number</i> | <i>Description</i> | | | | |
| ANT70-0500 | 2.4/5.0 GHz Dual-Band Antenna | | | | |
| DPE-101GI | 1-Port Gigabit PoE Injector | | | | |
| DWC-1000 | Unified Wireless Controller | | | | |
| DWS-3160-24TC | Unified Wireless L2 Gigabit PoE Switch | | | | |
| DWS-3160-24PC | Unified Wireless L2 Gigabit PoE Switch | | | | |
| DWS-4026 | L2+ Unified Wired/Wireless Gigabit Switch Switch - 24 ports | | | | |

¹ 300 Mbps is the maximum wireless signal rate as specified by the IEEE 802.11n standard. Actual data throughput will vary. The network and other factors, including volume of network traffic, building materials, and nearby radio interference may lower actual data throughput.

² Up to 16 virtual Access Points each on the 5GHz and 2.4 GHz radios

³ When used with a D-Link Unified Wireless Switch or Wireless controller

Updated 04/12/12

For more information

U.S.A. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com **Canada** | 2525 Meadowvale Blvd | Mississauga, ON L5N 5S2 | 800.361.5265 | dlink.ca

©2012 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo, and D-ViewCam are trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners. Visit www.dlink.com for more details.

D-Link[®]
Building Networks for People