

Wireless ADSL Router

With Firewall Protection/QoS Control

- Integrated ADSL, 802.11g Wireless LAN & 4-Port Switch
- High-Speed ADSL2/2+ Connection
- DoS & SPI Firewall Protection
- QoS & SNMP Management Support

FEATURES

Wireless ADSL Router

- Built-in ADSL Interface
- Built-in 802.11g WLAN Up to 54Mbps Speed
- Integrated 4-Port Ethernet Switch

High-Speed ADSL Access

- ADSL: G.992.1 G.dmt, G.992.2 G.lite, ANSI T1.413 Issue 2 (Full Rate DMT Over Analog POTS) Annex A
- ADSL2: G.992.3 (G.dmt.bis) Annex A
- ADSL2+: G.992.5 Annex A
- G.994.1 G.hs Auto-Negotiation of Different ADSL Flavors

Firewall/Access Security

- DoS Attack Prevention
- Stateful Packet Inspection (SPI)
- IP/MAC-Based Packet Filtering
- Port-Based VLAN

QoS/Bandwidth Control

- Traffic Prioritization With 4 Priority Queues
- IGMP Snooping Multicast

Easy Setup/Flexible Management

- Dynamic Domain Name System (DDNS)
- Universal Plug and Play (UPnP) Compliant
- Quick Installation Wizard
- Web-Based GUI for Local/Remote Management
- SNMP Management

The DSL-G624T wireless ADSL router is a versatile, high-speed remote router for home and the small office. With integrated ADSL2/2+ supporting up to 24Mbps download speed, firewall protection, Quality of Service (QoS), 802.11g wireless LAN and 4 Ethernet switch ports, this router provides all the functions that a home or small office needs to establish a secure and high-speed remote link to the outside world.

High-Speed ADSL Connection. The DSL-G624T features the latest ADSL2/ADSL2+ standards, providing speeds of up to 24Mbps downstream and 1Mbps upstream (ADSL2+), or 12Mbps downstream and 1Mbps upstream (ADSL2). This router auto-senses the connection type and auto-negotiates the best modulation scheme, using the G.hs (handshake) protocol.

Ready Wireless LAN & Ethernet Connection for Workgroup. The DSL-G624T provides an integrated 802.11g WLAN supporting wireless speeds of up to 54Mbps and interoperability with 802.11b wireless devices on the 2.4GHz frequency band. It also provides four 10/100Mbps Ethernet switch ports for ready workstations connection. These built-in functions save you the cost and trouble of installing a separate wireless access point and an Ethernet switch.

Firewall Protection. The router provides firewall security using Stateful Packet Inspection (SPI) and hacker attack logging for Denial of Service (DoS) attack protection. SPI inspects the contents of all incoming packet headers before deciding what packets are allowed to pass through. Access control is provided with packet filtering based on port and source/destination MAC/IP addresses. With Virtual Server Mapping, the router can be set to allow separate FTP, Web, and multiple games to share the same Internet-visible IP address while still protecting your servers and workstations from hackers. You can configure any of the built-in LAN ports of the router to function as a DMZ port. VPN pass-through is provided to let mobile users access files and mail from offices to work at home without having to use complex VPN client software.

Quality of Service Features. The DSL-G624T supports 4 priority queues to enable a group of home or office users to experience the benefit of smooth network connection of inbound and outbound data without concern of traffic congestion. This QoS support allows you to enjoy high ADSL transmission for applications such as VoIP, multimedia and on-line games over the Internet.



Technical Specifications

Hardware

Interfaces

- 1 RJ-11 ADSL port
- 4 RJ-45 10/100BASE-TX Fast Ethernet LAN switch ports with auto MDI/MDIX
- Built-in WLAN
- Factory reset button

Wireless LAN

- IEEE 802.11g standard
- Wireless speed: up to 54Mbps
- Frequency range: 2.4 GHz to 2.484G Hz
- 64/128 bits WEP data encryption
- Wi-Fi Protected Access (WPA) security

ADSL

Standards

- ADSL standards: ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 (G.lite) Annex A
- ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex A, ITU G.992.4 (G.lite.bis) Annex A
- ADSL2+ standards: ITU G.992.5 Annex A
- Auto-handshake: ITU G.994.1 (G.hs)

Data Rates

- G.dmt: 8Mbps downstream, 832Kbps upstream
- G.lite: 1.5Mbps downstream, 512Kbps upstream
- ADSL2: 12Mbps downstream, 1Mbps upstream
- ADSL2+: 24Mbps downstream, 1Mbps upstream

ATM & PPP Protocols

- ATM Adaptation Layer Type 5 (AAL5)
- Bridged or routed Ethernet encapsulation
- VC and LLC based multiplexing

- PPP over Ethernet (PPPoE)
- PPP over ATM (RFC 2364)
- Classical IP over ATM (RFC 1577)
- OAM F4/F5

Router

Network Protocols & Features

- NAT, Static Routing, RIP v.1, v.2
- Universal Plug and Play (UPnP) Compliant
- Dynamic Domain Name System (DDNS)
- Virtual Server & DMZ
- SNTp, IGMP proxy

Firewall/Access Security

- Built-in NAT firewall
- Stateful Packet Inspection (SPI)
- DoS attacks prevention (IP Spoofing, Land Attack, Smurf Attack, Ping of Death, TCP SYN flooding)
- Packet filtering based on port, source IP address, destination IP address, MAC address (ICMP/TCP/UDP)

Virtual Private Network (VPN)

- PPTP/IPSec pass-through

Configuration/Management

- Quick Installation Wizard
- Web-based GUI for remote/local management
- Firmware upgrade, configuration data upload/download via Web-based GUI
- Telnet server for remote/local management
- Syslog monitoring
- SNMP v.1, v.2c support using built-in MIB-II(RFC-1213)
- DHCP server/client

QoS Control

- LAN to WAN traffic prioritization/bandwidth management
- 802.1p traffic prioritization (4 queues)

Security/Bandwidth Management

- IGMP Snooping with 32 Multicast groups
- PVC/VLAN port mapping (4 VLANs)
- Bandwidth management based-on IP protocol, port number, MAC address

Physical & Environmental

Power Input

Through 12VAC 1.2A external power adapter

Dimensions

193 x 118 x 31 mm

Weight

336 grams

Operating Temperature

0° to 40°C

Storage Temperature

-20° to 70°C

Operating Humidity

5% to 95% non-condensing

Emission (EMC/EMI)

- FCC Part 15 Class B
- CE (EN55022/EN55024/EN300 328/EN301 489)

Safety

- CSA
- LVD



D-Link Worldwide Offices

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76
Europe (U. K.)	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
France	TEL: 33-1-30238688	FAX: 33-1-30238689	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	India	TEL: 91-022-26526696	FAX: 91-022-26528914
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-3908881
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Portugal	TEL: 351-21-8688493		Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099 #350
Czech Republic	TEL: 420-(603)-276-589		China	TEL: 86-10-58635800	FAX: 86-10-58635799
Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-1188
Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902	Headquarters	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299