


Fiber Gigabit PCI Express x4 Adapter

High-Performance Hardware

- + 802.3z 1000BASE-SX Standard
- + Up to 550 Meters' Multi-Mode Fiber Cable Distance
- + PCI-E 1.0a Interface With 2.5GHz Signaling
- + 802.3x Flow Control and Full-Duplex Operation
- + Laser Eye Safety Certified
- + Hot-Swappable

Advanced Functions

- + 9K Bytes Jumbo Frame
- + 802.1p Priority Queue QoS
- + 802.1Q VLAN Security
- + Promiscuous Mode
- + ACPI 2.0 Power Management
- + Simple Network Management Protocol Agent for Integration in SNMP Management
- + D-Link Network Control Program for Advanced Feature Setting



The D-Link DGE-560SX Fiber Gigabit PCI Express x4 Adapter is a high-performance network card that let businesses take advantage of the PCI Express (PCIe) slots of their servers to enhance network performance with fiber-optic connectivity. The adapter's dedicated input/output (I/O) bandwidth PCIe ensures priority performance without bus sharing for Gigabit Ethernet connectivity in fiber-optic networks.

PCI Express Interface

The DGE-560SX PCI Express x4 adapter supports 2Gbps data addressing to increase higher throughput requirements from the adapter's PC board to the server host. It provides unsurpassed robustness, reliability and performance, and is the optimum I/O connectivity solution for a wide spectrum of server, storage and system area networks (SAN). As the successor to the PCI and PCI-X interfaces, PCI Express bus architecture host serial bus eliminates many of the inefficiencies of parallel PCI and PCI-X architectures. With lower pin counts and lower power consumption requirements, the DGE-560SX PCI Express host bus adapter also reduces system level power requirements. PCI Express is backward compatible with PCI and PCI-X addressing, which allows all existing applications and Operating Systems to function unchanged.

Fiber-Optic Connection

Delivering network speed up to 2000Mbps (full-duplex) on the fiber-optic cable, the DGE-560SX adapter brings ample bandwidth to a server up to 550 meters away.

It offloads the host operating system overhead by providing on-board verification of IP header and TCP/UDP checksum for data received, in turn freeing up server processing power for other applications.

VLAN & QoS Support

The DGE-560SX adapter provides on-board screening of VLAN tagged Ethernet frames compliant with IEEE 802.1Q. This allows the server to operate in a flexible and secure network configuration in a standards-based environment. It supports 802.1p Priority Queues for improved delivery of time sensitive data such as voice and video.

Advanced Functions

The DGE-560SX supports other advanced features such as Jumbo Frame of up to 9KB and Promiscuous mode. It supports ACPI (Advanced Configuration and Power Interface) specifications to enable OS-directed configuration and Power Management (OSPM) to enumerate and configure server motherboards. The adapter supports SNMP agent for management under an SNMP-based platform.

Hot Swap Capability

It is often difficult or impossible to schedule downtime on a server to replace or install peripheral cards. As a PCI Express card, the DGE-560SX provides native support for hot plugging and hot swapping, which makes it ideal for installation in a server. This hot swap capability makes it easy for network administrators to add, change or remove I/O peripherals while minimizing the server downtime.




Fiber Gigabit PCI Express x4 Adapter

Technical Specifications

Standards	+ 802.3z 1000BASE-SX Gigabit Standard + PCI-E 1.0a Interface With 2.5GHz Signaling + 802.3x Flow Control
Power Requirement	Universal Bus 3.3V
Data Transfer Rate	Gigabit
Network Operation Mode	Full Duplex (2000Mbps)
Network Media & Transmission Range	+ 62.5/125 micron multi-mode fiber cable: up to 75 meters' distance + 50/125 micron multi-mode fiber cable: up to 550 meters' distance
Network Interface Connector	850nm LC fiber-optical connector
Installable PCI Slot	PCI Express x4/x8/x16
Supported Functions	+ 9K Bytes Jumbo Frame + 802.1p Priority Queue QoS + 802.1Q VLAN security + Promiscuous mode + ACPI 2.0 Wake on LAN Power Management + Simple Network Management Protocol Agent
Driver Support	+ Microsoft Windows 2000, 2000 server + Microsoft Windows 2003 server + Microsoft Windows 2003 x64 Edition + Microsoft Windows XP + Microsoft Windows XP x64 Edition + Linux for Kernel 2.4.x, 2.6.x
Diagnostic LED	Link/Activity
Dimensions	113 x 59.2 mm (4.45 x 2.33 inches)
Operating Temperature	0° C to 40° C (32° F to 104° F)
Storage Temperature	-25° C to 55° C (-13° F to 131° F)
Humidity	5% to 90% non-condensing
EMC & Safety	+ FCC Class B, ICES-003 + CE + VCCI + BSMI + C-Tick + Eye-viewing safety: Laser Class I EN60825-1 standard

**Auto-Run Installation Program**

The Auto-Run Installation Program provides a single-step installation of the DGE-560SX adapter in a Windows-based network server.

**Connecting the Server in the Network****D-Link Worldwide Offices**

U.S.A.	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Spain	TEL: 34-93-4090770	FAX: 34-93-4910795	Turkey	TEL: 90-212-289-56-59	FAX: 90-212-289-76-06
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Portugal	TEL: 351-21-8688493		Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Europe (U.K.)	TEL: 44-20-8955-9000	FAX: 44-20-8955-9001	Czech Republic	TEL: 420-(603)-276-589		Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300	Switzerland	TEL: 41-(0)-1-832-11-00	FAX: 41(0)-1-832-11-01	Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
France	TEL: 33-1-30238688	FAX: 33-1-30238689	Greece	TEL: 30-210-9914 512	FAX: 30-210-9916902	Brazil	TEL: 55-11-218-59300	FAX: 55-11-218-59322
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331	Luxemburg	TEL: 32-(0)2-517-7111	FAX: 32-(0)2-517-6500	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500	Poland	TEL: 48-(0)-22-583-92-75	FAX: 48-(0)-22-583-92-76	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099 #350
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	Hungary	TEL: 36-(0)-1-461-30-00	FAX: 36-(0)-1-461-30-09	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901	Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322	China	TEL: 86-10-58635799	
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-8168
Norway	TEL: 47-99-300-100	FAX: 47-22-309580	India	TEL: 91-022-26526696	FAX: 91-022-26528914	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9989
Finland	TEL: 358-9-2707 5080	FAX: 358-9-2707-5081	Middle East (Dubai)	TEL: 971-4-3916480	FAX: 971-4-390881			