



Pocket-size Print Server

The DP-301P+ print server is a compact pocket-sized print server which connects your Ethernet network directly to your printer, wherever it is. It manages the flow of print files from your workstations or file servers to its connected printers, delivering print jobs to high-performance printers much faster than a file server or a PC acting as a print server can. The printer server is equipped with a high-speed parallel printer port, allowing you to share the latest generation of bi-directional laser printers, color ink jets and others. It plugs directly to the back of a parallel printer, which is shared among multiple users and no printer cable is required.

Key Features

- Equipped with a standard 36 pin port that plug directly to the back of any parallel printer
- Auto-sensing 10/100Mbps Fast Ethernet port
- Multiple protocol support ideal for shared printing in LAN environments
- Bi-directional communication allows to collect information about attached printer's status
- Supports SNMP and MIB2 (RFC 1213)
- Flash Memory For Easy Software Upgrade
- Web Configuration Supported

Technical Specifications

Print Server

Printer Connection

Standards

IEEE 1284 Bi-directional parallel interface

Ports

- Bi-directional 36-pin parallel port
- 10/100Mbps Fast Ethernet Port

Parallel Port Bi-directional Communication

Hewlett-Packard PJI (Printer Job Language) supported

Network Protocols

Transport Protocols

TCP/IP, NetBEUI, AppleTalk/EtherTalk

TCP/IP Protocols Supported

BOOTP, SNMP, Telnet, TFTP, FTP, LPD, RARP, DHCP

Management and Diagnostics

Standard

SNMP

MIBs

MIB-II (RFC 1213)

Diagnostic LED Indicators

Power/Tx, Link/Rx, LPT

Environmental and Physical

Power Supply

DC 5V/2.4A

Dimensions

92.8mm x 58mm x 25.3mm

Weight

Approx. 65g

Operating Temperature

0 - 50° C (32° - 122° F)

Storage Temperature

-25 - 55° C (-13° - 131° F)

Humidity

5% to 95% non-condensing

Emissions

- FCC Class A
- CISPR 22 Class A
- VCCI Class A

Safety

- UL (UL 1950)
- CSA(CSA 950)
- TUV/GS (EN 60950)



Ordering Information

DP-301P+/A	(with USA power adapter in worldwide version)
DP-301P+/B	(with U.K. power adapter in worldwide version)
DP-301P+/E	(with Europe power adapter in worldwide version)
DP-301P+/N	(with Australia power adapter in worldwide version)
DP-301P+/U	(without power adapter in worldwide version)

D-Link®

Specifications subject to change without prior notice.

D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.



RECYCLABLE

Rev.01 (Oct. 2001)
Printed in Taiwan

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033	www.dlink.com
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095	www.dlink.ca
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
U.K	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300	www.dlink.de
France	TEL: 33-1-30-23-86-88	FAX: 33-1-30-23-86-89	www.dlink.france.fr
Benelux	TEL: 31-40-2668713	FAX: 31-40-2668066	www.dlink-benelux.nl
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	www.dlink.it
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795	www.dlinkiberia.es
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901	www.dlink.se
Norway	TEL: 47-22-991890	FAX: 47-22-207039	
Denmark	TEL: 45-43-96-90-40	FAX: 45-43-42-43-47	www.dlink.dk
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661	www.dlink.fi.com
Singapore	TEL: 65-774-6233	FAX: 65-774-6322	www.dlink-intl.com
Australia	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077	www.dlink.com.au
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868	www.dlink.com.jp
China	TEL: 86-10-88097777	FAX: 86-10-88096789	
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914	www.dlink-india.com
Middle East	TEL: 20-2-6356176	FAX: 20-2-6356192	www.dlink-me.com
South America	TEL: 56-2-232-3165	FAX: 56-2-232-0923	www.dlink.cl
Russia	TEL: 27(0)126652165	FAX: 27(0)126652166	www.d-link.co.za
Taiwan	TEL: 7-095-737-3389	FAX: 7-095-737-3390	www.dlink.ru
D-Link Corp.	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515	www.dlinktw.com.tw
	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299	www.dlink.com.tw