

AirPro



DWL-AB520

Dualband PCI card with a high Gain omni-directional antenna, extend from the card through an antenna cable.

Dualband 802.11a/b Wireless LAN PCI Card

The D-Link AirPro DWL-AB520 is a powerful dualband wireless LAN PCI card for desktop PCs. This PCI card connects you to networks operating on both 5GHz and 2.4GHz frequency bands, giving you flexible access to both 802.11a and 802.11b types of networks. Transmission speeds are up to 11Mbps for 802.11b, and 54Mbps for 802.11a. With industry standard interoperability, strong data encryption security and flexible frequency band support, this card gives you the true mobility and fast, secure connection to wireless networks.

Dual-band Wireless Access

The DWL-AB520 connects you to wireless Access Points, Internet gateways, servers, wireless users and peripherals no matter if they operate on 5GHz or 2.4GHz frequency band. Communication with 802.11a and 802.11b networks is transparent, with transmission and reception dynamically matching the available speed of the connecting node. The card strictly complies with IEEE 802.11a and 802.11b standards and interoperates with all 802.11a and 802.11b compliant devices.

Flexible High-speed Connection

In a predominantly 802.11b environment, the DWL-AB520's dualband capability allows you to plan for future network growth to immediately tap into 802.11a resources when available wireless channels become available. The additional high-bandwidth channels available with 802.11a also offer you a robust way to transmit large data files much quicker than possible with 802.11b.

Network Security

Your data transmitted and received in the air is well protected by a security scheme. The DWL-AB520 provides 64/128/152-bit industry-standard WEP (Wired Equivalent Privacy) data encryption. Data privacy mechanism is based on a shared key algorithm, as described in the wireless LAN standard. In addition, AES enhanced security and 802.1x for user authentication provide a much more formidable barrier to hackers and sniffers, allowing you to securely share data over the network.

Powerful Antenna

The DWL-AB520 features a high Gain external antenna that can be positioned in any number of configurations to achieve the best possible signal.

Easy Installation

With PCI plug-and-play capability, the DWL-AB520 can be easily installed into a PC to provide connectivity directly to any wireless device in the ad-hoc mode or infra-structure mode. Access to wired Ethernet servers is also provided through wireless LAN Access Points.

Key Features

- PCI 2.2 card with Bus Master direct data transfer to PC host
- IEEE 802.11a/b industry standards compliant
- 2.4GHz and 5GHz dualband support
- Up to 54Mbps (108Mbps Turbo mode for FCC regulation) speed for 802.11a, 11Mbps for 802.11b
- 64/128/152-bit WEP data encryption & Advanced Encryption Security (AES)
- Supports Windows 98, 2000, ME, XP
- DFS/TPC for European operation support
- Easy-to-use configuration and diagnostic utilities
- Wi-Fi™ & Wi-Fi5™ compliant

DWL-AB520

Technical Specifications

5GHz & 2.4GHz Wireless LAN

Standards

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.1x
- PCI 2.2 Local Bus

Media Access Control Protocol

CSMA/CA with ACK

Network Architecture Types

- Ad-Hoc mode
- Infrastructure mode

Frequency Range (802.11a)

- US & Canada: 5.15 - 5.350GHz & 5.725 - 5.825GHz
- Japan: 5.15 - 5.25GHz
- Europe: 5.15 - 5.35GHz

Frequency Range (802.11b)

2400 - 2.497GHz

Operating Channels (802.11a)

- US & Canada: 12
- Europe: 8
- Japan: 4

Operating Channels (802.11b)

- US: 11
- Europe: 13 (Except Spain and France)
- Japan: 14

Data Rates

- 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
- 802.11b: 1, 2, 5.5, 11 Mbps

Encryption

- Advanced Encryption Security (AES)
- 64/128/152-bit WEP (Wired Equivalent Privacy)

Radio & Modulation Technology

- 802.11a: OFDM (Orthogonal Frequency Division Multiplexing)
- 802.11b: DSSS (Direct Sequence Spread Spectrum)

Antenna

4dBi Gain extended omni-directional external antenna

Transmitter Output Power

- 802.11a: +13 - 14 dBm (54Mbps)
- 802.11b: +18 dBm (11Mbps)

Receiver Sensitivity

- 802.11a: -70 dBm (54Mbps)
- 802.11b: -84 dBm (11Mbps)

Range Coverage (Open Environment)

- Indoors: Up to 100 meters (328 feet)
- Outdoors: Up to 400 meters (1,312 feet)

Physical & Environmental

Diagnostic LEDs

- Power
- Link/Activity

Operating Voltage

3.3V +/- 10%

Power Consumption

- Transmission: 900 mA (max.)
- Reception: 760 mA (max.)

Dimensions

120 (L) x 65 (W) x 7 (H) mm
(4.7 x 2.56 x 0.28 inches)

Weight

100 grams (0.22 lb.)

Operating Temperature

0° - 55 °C (32° - 131° F)

Storage Temperature

-20° - 75 °C (-4° - 167° F)

Non-Operating Humidity

5% - 95% non-condensing

Operating Humidity

10% - 90% non-condensing

Emission (EMI)

- FCC Class B
- CE Class B

Compliance

- Wi-Fi™
- Wi-Fi5™

OS Support

Windows 98SE, ME, 2000, XP



Ordering Information

DWL-AB520

IEEE 802.11a/b Dualband Wireless LAN
PCI Card

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A.	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
U.K.	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Benelux	TEL: 31-10-204-5740	FAX: 31-10-204-5880
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
Norway	TEL: 47-22-991890	FAX: 47-22-205700
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-010-8518-2533	FAX: 86-010-8518-2250
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 202-6356176	FAX: 202-6356192
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-3094-2910	FAX: 55-11-3094-2921
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 01 (Nov. 2002)
Printed in Taiwan