



Optical Fiber Fast Ethernet Card

The DFE-550FX is a high-performance Fast Ethernet card that connects your desktop PC to a reliable fiber network. The card plugs into a PCI expansion slot inside your PC, transmits data at 100Mbps half duplex or 200Mbps full duplex. Supporting advanced functions including traffic priority queues and VLAN, this card provides a secure environment to let you run bandwidth-demanding applications, such as IP telephony and video conferencing.

Reliable Fiber Connection

The DFE-550FX card allows you to establish secure fiber link for your PC. It can be used to set up a power workstation or a server with a direct fiber connection to a Fast Ethernet switch. Capable of running at 200Mbps full-duplex, this card serves well in a high electro-magnetic interference environment, providing a cable distance of up to 2 km to the switch.

Wake-On-LAN Power Management

The card supports Advanced Configuration Power Interface (ACPI) Wake-On-LAN (WOL), allows your computer to be powered ON/OFF from a remote place. Providing a great utility for power management of the PC, this function allows the administrator to send a wake-up signal to the computer to initiate action at irregular times and from distant locations.

High Performance

With 32-bit bus master operation, the card guarantees the highest performance. Bus master transfers data directly between the card and the host at multi-megabits per second, bypass the host CPU to alleviate its workload.

Flow Control to Minimize Packet Loss

The card's embedded flow control provides a means to protect against possible data loss during transmission on the network. When connected to a Fast Ethernet switch that supports flow control, the card receives signals from the switch regarding buffer overrun during peak usage periods. The card then delays transmission until the switch is ready again to accept new data.

VLAN to Improve Performance and Security

The card supports IEEE 802.1Q multiple Virtual LAN, allowing you to segment the network to smaller domains to improve performance and security. Dissemination of broadcast and unnecessary computer-to-computer packets can be restricted to reduce extraneous traffic. The card provides a VLAN table for the following functions: filtering packets by recognizing VLAN Tags, stripping VLAN Tags on receive, and inserting VLAN Tags on transmit.

IEEE 802.1p Priority Queues Support

With packet prioritization capability, the card allows traffic to be queued as critical and non-critical, permitting your computer to run voice over IP, video-conference and multimedia applications where packets are delivered at best-effort speeds.

RPL and PXE Remote Boot Options

2 remote boot options are available for selection. Administrators can choose to set up a security scheme for diskless workstations to boot from servers using (1) the traditional Remote Program Load (RPL) or (2) Intel's Pre-boot Execution Environment (PXE). Stations with boot ROMs installed on the on-board socket can boot O.S. from NetWare, NT and other servers to run applications designated by the administrator.

Key Features

- 100Mbps Fast Ethernet fiber connection
- 32-bit PCI bus master operation
- Full/half duplex support
- Wake-on-LAN (WOL) for power management
- IEEE 802.3x full-duplex flow control
- IEEE 802.1Q VLAN support
- IEEE 802.1p priority tagging
- Runs Win95, 98, 2000, NT, NetWare, Linux
- Optional boot ROM for remote program load from servers

Technical Specifications

Fast Ethernet Fiber Card



General

Standards

- IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper)
- PCI local bus 2.2 specifications
- IEEE 802.3x Flow Control
- IEEE 802.1Q VLAN tagging
- IEEE 802.1p priority tagging
- Advanced Configuration and Power Interface (ACPI) v.1.0

Topology

Star

Protocol

CSMA/CD

Network Data Transfer Rates

- 100Mbps (half-duplex)
- 200Mbps (full-duplex)

Network Cable

62.5/125 micron multimode fiber-optics (2km at full-duplex, 412m at half-duplex)

Fiber Connector

SC

Diagnostic LED Report

- Link
- Activity (Tx/Rx)
- Full duplex

Cache Buffer

- 2K bit receive FIFO
- 2K bit transmit FIFO

Flow Control

- IEEE 802.3x flow control per for full duplex
- Back pressure in half duplex

System Setup

IRQ

Allocated by system

I/O Address

Allocated by system

Full/half Duplex

- Auto-detected upon connection to network device
- User-selectable through software

Environmental & Physical

Power Consumption

1.5 watts (maximum)

Dimensions

120 x 73 mm (4.73 x 2.88 inches)

Weight

120g (0.26 lb.)

Operating Temperature

0° - 50°C (32° - 122° F)

Storage Temperature

-25° - 55°C (-13° - 131° F)

Humidity

10% - 90% non-condensing

Emission (EMI)

- FCC Class B
- CE Class B
- C-Tick
- BSMI Class B

Network O.S. Support

- Novell NetWare Client ODI
- Novell NetWare Server 3.12, 3.2, 4.1x, 5.x
- Microsoft NDIS drivers 3.x, 4.x, 5.x
- Microsoft Windows 95, 98, 2000
- Microsoft NT 4.0
- Linux kernel 2.0.x, 2.2.x

Remote Boot (Optional)

Boot ROM Address

Searched by system BIOS

Boot ROM Flash Memory

- RPL boot ROM: 2KB
- PXE boot ROM: 2KB

Boot Servers Supported

- Novell RPL Boot ROM code
- NetWare 3.x, 4.x RPL server
- Microsoft Windows NT 3.51, 4.x RPL server
- Intel PXE 2.0



Ordering Information

Fast Ethernet Fiber Card

DFE-550FX 100BASE-FX Fast Ethernet fiber PCI card (SC connector)

Remote Boot ROMs

DFE-554FR RPL boot ROM for DFE-550FX
DFE-554FP PXE boot ROM for DFE-550TX

D-Link®

Specifications subject to change without prior notice.

D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
U.K	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511
Germany	TEL: 49-61-96779900	FAX: 49-61-967799300
Benelux	TEL: 31-40-2668713	FAX: 31-40-2668666
France	TEL: 33-1-30.23.86.88	FAX: 33-1-30.23.86.89
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723
Spain	TEL: 34-93-4965751	FAX: 34-93-4965701
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901
Norway	TEL: 47-22-991890	FAX: 47-22-207039
Denmark	TEL: 45-43-96.90.40	FAX: 45-43-42.43.47
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661
Singapore	TEL: 65-774-6233	FAX: 65-774-6322
Australia	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-88097777	FAX: 86-10-88096789
India	TEL: 91-22-652-6696	FAX: 91-22-652-8914
Middle East	TEL: 20-2-2456176	FAX: 20-2-2456192
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE

Rev.01 (Aug. 2001)

Printed in Taiwan

7DFE550FX010