



RANGEBOOSTER G™ MULTIFUNCTION PRINT SERVER

ALWAYS READY

Print when you need to without booting up a host PC

PRINT AND SCAN

Industry's first wireless multifunction print server – tested with over 100 different printer models

ENHANCED NETWORKING

Wirelessly share up to 4 printers or multifunction printers on your network



FOUR PRINTERS, LESS WAITING

The D-Link RangeBooster G™ Multifunction Print Server (DPR-1260) is D-Link's most versatile and easiest to use Print Server yet. When attaching multiple devices, the Quick Installation Wizard takes all the work out of setting up the Print Server and configuring the attached printers. Multiple ports give you the option of adding multiple printers or multifunction printers to the network. RangeBooster G technology improves wireless performance, reducing the time required to send print jobs to the print server.

PRINTERS AND MULTIFUNCTION PRINTERS WELCOME!

Tested with over 100 different printer models, this Print Server offers class-leading device compatibility¹. Using the web-based interface, easily scan documents and photos directly to your computer. This print server is compatible with a wide range of USB multifunction printers including the scanning functionality of select multifunction printers and is backward compatible with USB 1.1/1.0 printers.¹

WIRELESS EXPANDABILITY

The Ethernet port on the Print Server can be used as a wireless bridge. This provides wireless connectivity for any Ethernet-enabled device, such as a computer, Digital Video Recorder (DVR), or Network-Attached Storage (NAS) to the wireless network.

WHAT THIS PRODUCT DOES

D-Link's new RangeBooster G™ Multifunction Print Server (DPR-1260) allows you to wirelessly share up to 4 USB Multifunction Printers (MFP) on your network. This innovative new print server allows multiple users to print using one of the four connected MFPs¹. By supporting multiple printers over a wireless connection, the DPR-1260 is the ideal solution for your home, classroom, or office.

PRINT, SCAN AND CONNECT

Simply plug your USB printer into one of the four ports, run the automatic configuration wizard, and you are ready to start printing and scanning over your wireless network¹. For extra network connectivity, you can also use the DPR-1260 to provide wireless connectivity to any Ethernet-enabled device, such as a computer or Network-Attached Storage (NAS).



COMPATIBLE PRINTER LIST¹

SCAN & PRINT SUPPORT

Epson®	OfficeJet 7300
Stylus CX3810	OfficeJet 7310
Stylus CX4800	OfficeJet 7410
Stylus CX5100	Photosmart 2575
Stylus CX6400	Photosmart 3210
Stylus Photo RX600	Photosmart 3310
	Photosmart C4180
	PSC 1210
Hewlett-Packard®	PSC 1311
OfficeJet 4110	PSC 1315
OfficeJet 4215	PSC 1350
OfficeJet 4315	PSC 1410
OfficeJet 5505	PSC 1510
OfficeJet 5510	PSC 1600
OfficeJet 5610	PSC 1610
OfficeJet 6 122	PSC 2175
OfficeJet 6110	PSC 2350
OfficeJet 6127	PSC 2355
OfficeJet 6210	PSC 2410
OfficeJet 7110	PSC 2510
OfficeJet 7130	PSC 2710
OfficeJet 7200	
OfficeJet 7210	

PRINT ONLY SUPPORT

FOR A LIST OF COMPATIBLE PRINTERS THAT PROVIDE PRINT ONLY SUPPORT, PLEASE VISIT <http://support.dlink.com>



TECHNICAL SPECIFICATIONS

STANDARDS

- + IEEE 802.11g + IEEE 802.11b
- + IEEE 802.3 + IEEE 1284
- + USB 2.0

PORTS

- + Power + 4 x USB 2.0 Ports
- + 10/100 LAN Port

WIRELESS SIGNAL RATES² WITH AUTOMATIC FALLBACK

- 108, 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, & 1Mbps

WIRELESS FREQUENCY RANGE

- 2.4GHz to 2.462GHz

WIRELESS TRANSMIT POWER

- 15dBm ± 2dBm

EXTERNAL ANTENNA TYPE

- Single Detachable Reverse SMA

MODULATION TECHNOLOGY

- + Orthogonal Frequency Division Multiplexing (OFDM)
- + Complementary Code Keying (CCK)

SECURITY

- + 64/128-bit WEP
- + Wi-Fi Protected Access (WPA™-PSK)

TRANSPORT PROTOCOL

- TCP/IP

PRINTING PROTOCOLS

- + LPD + LPR + RAW

DEVICE MANAGEMENT

- + Internet Explorer v6 or Later; or other Java-enabled Browsers
- + DHCP Server and Client

DIAGNOSTIC LEDs

- + Power + Link/Activity
- + WLAN (Wireless Connection) + USB x 4

CERTIFICATIONS

- FCC Class B, IC

OPERATING TEMPERATURE

- 32°F to 104°F (0°C to 40°C)

OPERATING HUMIDITY

- 95% Maximum (Non-condensing)

DIMENSIONS

- + Item: (WxHxD): 5.59" x 1.22" x 4.29"
- + Packaging: (WxHxD): 10.8" x 8.23" x 2.68"

WEIGHT

- + Item: 0.46 lbs
- + Packaging: 1.75 lbs

WARRANTY

- 1-Year Limited³

¹ For a list of compatible printers, visit <http://support.dlink.com>.

² Maximum wireless signal rate derived from IEEE Standard 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

³ 1-Year Limited Warranty available only in the U.S.A. and Canada.

⁴ Computer must adhere to Microsoft's recommended System Requirements.

⁵ The software included with this product is not Mac-compatible.

⁶ Latest software and documentation are available at <http://support.dlink.com>.

All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

MINIMUM SYSTEM REQUIREMENTS

- + 10/100 Fast Ethernet Wired or 802.11b/g Wireless Network
- + Printer with USB Port¹
- + Computer with:
 - Windows® XP SP2 or Windows 2000 SP4² or Mac OS® X (v10.4/v10.3)³
 - Internet Explorer v6 or Mozilla Firefox
 - CD-ROM Drive
 - Network Interface Card

PACKAGE CONTENTS

- + RangeBooster G™ Multifunction Print Server
- + Detachable Antenna
- + CAT5 Ethernet Cable
- + Power Adapter
- + CD-ROM⁴ with
 - Installation Wizard
 - Product Documentation