



Multiport, Multiprotocol Print Servers

D-Link's multiprotocol print servers turn any printer into a network printer through a simple plug to the printer port. Supporting multiple protocols and multiple high-speed printer ports, these compact hand-held devices bring a high level of flexibility, performance and convenience to printer sharing over the network.

2 Flexible Choices

2 models are available: one providing lower cost through dedicated connection to 10Mbps Ethernet, the other offering flexible attachment to 10BASE-T or 100BASE-TX. A combo 10BASE-T/BNC interface is provided for the dedicated model, while an auto-negotiate NWay port is provided for the 10/100Mbps device.

2 Parallel Ports, 1 Serial Port

Each model is equipped with 2 high-speed parallel ports, and 1 serial port transmitting at up to 57.6Kbps. This allows simultaneous connection to as many as 3 printers while eliminating PC printer port bottlenecks and reducing demands on network servers.

Multiprotocol Support

Supporting IP, NetBEUI and Apple EtherTalk protocols, these print servers are ideal for shared printing in mixed-LAN environments.

Bi-directional Communication

Both parallel ports support HP P/L protocol for bi-directional network printer communication, proactively providing the administrator with critical information about the network printers.

Versatile Administrative Program

An simple-to-operate GUI under Windows makes it possible to set up the print servers in the matter of minutes. Telnet support means that the administrator can also configure and maintain the print servers from any station on a Unix or TCP/IP network.

Performance, Convenience

With multiple high-speed ports and large spool buffers, D-Link's print servers provide outstanding performance over PC-based print servers and PC parallel/serial connections. The print server' compact size makes it possible to place them next to the printers, and to relocate the printers anytime, anywhere on the network.

Key Features

- Choices of auto-sensing 10BASE-T/BNC and 10/100Mbps NWay interface
- IEEE 1284-compliant high-speed parallel ports
- Serial port baud rate up to 57.6Kbps
- Easy configuration through Windows, Telnet, Web browser
- Support Windows NT, Windows 95, 98, 2000, ME, TCP/IP, Unix, AppleTalk
- Latest MIB-II (RFC 1213) for SNMP-standard management
- Flash memory for easy software upgrade

Technical Specifications

Printer Interface

Serial Port

- 1 DB-9 DCE RS-232 port
- XON/XOFF software flow control
- DTR/RTS hardware flow control
- 57.6Kbps baud max.

Parallel Ports

- 2 IEEE 1284-compliant ports
- Support bi-directional HP P/L protocol

LAN

Standards

- IEEE 802.3 10BASE-T Ethernet
- IEEE 802.3u 100BASE-TX Fast Ethernet
- ANSI/IEEE 802.3 NWay auto-negotiation

Protocol

CSMA/CD

Data transfer Rates

- Ethernet: 10Mbps
- Fast Ethernet: 100Mbps

Topologies

- 10BASE-T, 100BASE-TX: star
- 10BASE2: bus

Network Cables

- 10BASE2:
 - RG-58A/U 50-ohm thin coaxial cable (185m)
- 10BASE-T:
 - 2-pair UTP Cat. 3,4,5 (100m)
 - EIA/TIA-568 100-ohm screened twisted-pair (STP) (100m)
- 100BASE-TX:
 - 2-pair UTP Cat. 5 (100m)
 - EIA/TIA-568 100-ohm screened twisted-pair (STP) (100m)

Number of LAN Ports

- DP-100+: 1 auto-sensing RJ-45/BNC
- DP-300+: 1 auto-negotiate NWay RJ-45

LED Report

Power/Tx, Link/Rx, LPT1, LPT2, COM

Supported Frame Type

- IEEE 802.2
- IEEE 802.3
- Ethernet - II
- Ethernet - SNAP

Supported Network Protocols

- TCP/IP
- NetBEUI
- AppleTalk/Ether Talk

Print Servers

Physical & Environmental

Power Supply

DC 5V 2.4A

Operating Temperature

0° ~ 50°C

Storage Temperature

-10° ~ 50°C

Humidity

10% ~ 90% non-condensing

Dimensions

190 x 116.8 x 30.9 mm

Weight

360 grams

Emission (EMI)

- FCC Class A
- CE Mark A
- C-Tick Class A

Safety

- UL (UL 1950)
- CSA (CSA950)
- TUV/GS (EN60950)

Ordering Information

Multiprotocol Print Servers

DP-100+ 2 parallel, 1 serial, 1 combo, 10BASE-T/BNC port

DP-300+ 2 parallel, 1 serial, 1 NWay, 10/100Mbps port

Please specify your model number as follows:

- /U Includes no AC power adapter
- /E Includes an EU Standard AC power adapter
- /B Includes an UK Standard AC power adapter
- /A Includes an America Standard AC power adapter
- /N Includes an Australia standard AC power adapter

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc.
All other trademarks belong to their proprietors.

U.S.A	TEL: 1-949-788-0805	FAX: 1-949-753-7033	www.dlink.com
Canada	TEL: 1-905-829-5033	FAX: 1-905-829-5095	www.dlink.ca
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
U.K	TEL: 44-20-8731-5555	FAX: 44-20-8235-5511	www.dlink.co.uk
Germany	TEL: 49-61-96779900	FAX: 49-61-96779900	www.dlink.de
France	TEL: 33-1-30.23.86.88	FAX: 33-1-30.23.86.89	www.dlink.france.fr
Benelux	TEL: 31-40-2668713	FAX: 31-40-2668666	www.dlink-benelux.nl
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	www.dlink.it
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795	www.dlinkiberia.es
Sweden	TEL: 46-(0)8-564-61900	FAX: 46-(0)8-564-61901	www.dlink.se
Norway	TEL: 47-22-991890	FAX: 47-22-207039	www.dlink.no
Denmark	TEL: 45-43-96.90.40	FAX: 45-43-42.43.47	www.dlink.dk
Finland	TEL: 358-9-622-91660	FAX: 358-9-622-91661	www.dlink.fi.com
Singapore	TEL: 65-774-6235	FAX: 65-774-6322	www.dlink-intl.com
Australia	TEL: 61-2-9417-7100	FAX: 61-2-9417-1077	www.dlink.com.au
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9668	www.dlink.co.jp
China	TEL: 86-10-88097777	FAX: 86-10-88096789	www.dlink.com.cn
India	TEL: 91-22-652.6696	FAX: 91-22-652.8914	www.dlink-india.com
Middle East	TEL: 20-2-6356176	FAX: 20-2-6356192	www.dlink-me.com
South America	TEL: 56-2-232-3185	FAX: 56-2-232-0923	www.dlink.cl
South Africa	TEL: 27(0)126652165	FAX: 27(0)126652186	www.d-link.co.za
Russia	TEL: 7-095-737-3389	FAX: 7-095-737-3390	www.dlink.ru
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515	www.dlinktw.com.tw
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299	www.dlink.com.tw



RECYCLABLE

Rev.01 (Dec. 2001)
Printed in Taiwan