Hub USB-C 5-en-1 avec HDMI sans fil

DUP-501

Caractéristiques

- Hub USB-C tout-en-un pour répondre à tous vos besoins de connectivité nomade : stockage, périphériques et affichage
- Transfert de fichiers sans attente – USB 3.0 offre des vitesses allant jusqu'à 5 Gbit/s
- Affichage haute qualité pour vos présentations et divertissements – Sortie HDMI prenant en charge HDMI filaire en 3840×2160 @60 Hz et HDMI sans fil en 1920×1080 @60 Hz
- Bouton frontal pour basculer entre les modes d'affichage HDMI filaire et sans fil
- Pass-through PD jusqu'à 100 W pour recharger votre ordinateur portable et alimenter les périphériques connectés via un adaptateur USB-C
- Plug & Play – aucune installation de pilote requise. Branchez et utilisez immédiatement
- HDMI sans fil fonctionnant sur la bande 5 GHz, réduisant la congestion

Cas utilisateurs

Connectivité intégrée

Des connecteurs polyvalents associés à un HDMI sans fil offrent une connectivité filaire et sans fil pour une flexibilité optimale

Optimisez votre productivité

Le hub se connecte à une variété de périphériques et d'appareils pour optimiser votre espace de travail

Recharge en pass-through

Port PD jusqu'à 100 W pour une recharge rapide et des périphériques toujours alimentés

Rétrocompatible

Les ports USB et HDMI sont entièrement compatibles avec les anciens appareils prenant en charge les générations précédentes

Gardez votre bureau organisé

Le hub tout-en-un peut être connecté à l'avant ou à l'arrière pour s'adapter à tout design de PC ou d'ordinateur portable, et ainsi garder votre bureau dégagé

Facile et performant

Aucune installation de pilote requise grâce au Plug & Play – l'USB 3.0 offre un transfert de données haute vitesse tandis que l'HDMI 2.0 délivre des images réalistes

Fiable et stable

Transmission sans fil des signaux HDMI sur la bande 5 GHz, avec beaucoup moins d'interférences que la bande 2,4 GHz, pour des visuels plus clairs où que vous en ayez besoin

Le meilleur partenaire nomade

Simplifiez votre espace de travail tout en améliorant la communication grâce à une vitesse de connexion et une qualité de transmission supérieures, que vous soyez au bureau, à la maison ou en déplacement

Spécifications Techniques

General	
USB-C Hub Interfaces[1,3]	**Video Port:** • 1 x wired HDMI 2.0 (3840x2160@60Hz) **USB Ports:** • 2 x USB 3.0 Type-C: 5 Gbps • 1 x USB 3.0 Type-A: 5 Gbps **PD-in Port:** • USB Type-C: supports USB Power Delivery (PD 3.0) 100W power pass-through for fast charge **Button:** • Switch between wired and wireless HDMI mode **Host Connector:** • USB 3.1 Type-C with cable: 10 Gbps with USB Power Delivery (PD 3.0) 85W for fast charge
Wireless HDMI Receiver Interfaces	• 1 x HDMI 1.2 (1920x1080@60Hz) • Transmission distance limit: 30 m • 1 x USB-A: requires power of 5V@1A
Display Resolution[2]	• HDMI 2.0: 4K (3840x2160@60Hz) for wired HDMI and 1920x1080@60Hz for wireless HDMI
LED	• Green: Power on, Hub Mode • Green: Power on, Wired HDMI Mode • White: Power on, Wireless HDMI Mode
Supported System	
Operating System	macOS, Windows 11, Windows 10, and Android
Physical	
Dimensions	**USB-C Hub:** 90 x 55 x 15 mm **Wireless HDMI Receiver:** 27.5 x 18.5 x 10 mm
Weight	**USB-C Hub:** 61.5 g **Wireless HDMI Receiver:** 22.3 g
Operating Temperature	0 to 40 ℃
Storage Temperature	-20 to 65 ℃
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Certifications	FCC CE HDMI
Package Contents	
DUP-501	5-in-1 USB-C Hub Quick Installation Guide Warranty Card

1. Backward compatible with previous USB versions.
2. Resolutions based on DP 1.4 of the input signal of the connected device. If the input signal of the connected device is compatible with DP 1.2 graphics on Windows, only 4K (3840x2160@30Hz) can be supported as the max resolution.
3. Incompatible with TEAMGROUP MP44 M.2 PCIe 4.0 SSD (TM8FPW008T0C101)
4. Actual performance may vary due to settings, cabling, temperature, network configuration, interface, device compatibility, environmental and on-site conditions, and other similar factors. References to power capability, signal or processing speed, signal range or distance, data encryption, storage capacity, display properties, or other performance metrics are based on optimal conditions derived from industry standards and provided for informational purposes only. Specifications may be subject to change without prior notice.

D-Link (Europe) Ltd, 3rd Floor, 166 College Road, Harrow HA1 1BH, United Kingdom

Specifications are subject to change without notice. ©2025 D-Link. All Rights Reserved. D-Link and the D-Link logo are trademarks or registered trademarks of D-Link. All other third-party marks mentioned herein may be trademarks of their respective owners.

v1.00 EU