



## Gigabit Layer 3 Switch

### 12-Port Gigabit Switch With 4 Combo 1000BASE-T/SFP

The DGS-3312SR switch is a powerful, function-rich Layer 3 switch that gives the network administrator the flexibility to use it as an all-Gigabit Modular Switch supporting copper and fiber connections. With redundant power backup, modular configuration, Layer 3 packet routing and extensive management capability, this highly versatile switch gives you the functions and flexibility needed to set up and run a departmental/enterprise network for mission-critical applications.

#### Modular Architecture

The DGS-3312SR provides 4 10/100/1000BASE-T ports, 4 combo SFP (mini GBIC) slots and 2 open expansion slots. The expansion slots allow you to flexibly deploy this switch as a stand-alone all-Gigabit switch. The expansion slots support the following expansion modules:

- **DEM-340MG** 4-port SFP (mini GBIC) module. This module provides 4 SFP slots for installation of 4 Gigabit transceivers supporting short, medium and long distance fiber cables.
- **DEM-340T** 4-port copper Gigabit module. This module provides 4 10/100/1000BASE-T ports for 4 copper Gigabit connections.

#### 12-Port Collapsed Backbone

If you opt to use your DGS-3312SR as a stand-alone Gigabit switch, you can install up to 2 Gigabit modules in the expansion slots. This will give you 8 Gigabit ports, in addition to the 4 built-in 1000BASE-T/combo SFP ports, making it a total of 12 Gigabit ports. This type of deployment gives you a small collapsed backbone to which 12 switches and servers can be attached. All ports on the DGS-3312SR support jumbo frames to alleviate heavy network traffic. Copper and fiber cables can be deployed, depending on your selection of the port modules.

#### Redundant Power Support

The DGS-3312SR can be connected to an external power supply for redundant power backup purposes. In case the built-in internal power supply fails, the optional redundant power supply unit will automatically provide all the required power to ensure continuous operation.

#### Wire-speed IP Routing

The switch provides basic IP routing, with instant support for Windows, Unix and Internet environments. It provides wire-speed non-blocking switch fabrics with hardware-based packet filtering/forwarding. Packet routing is performed by on-board ASICs at speeds many times faster than CPU-based routers.

#### Seamless Integration

The DGS-3312SR can be instantly integrated into any existing network for seamless integration of Layer 2 and Layer 3 packet switching. With multi-layer support for every port, you can start with Layer 2 switching, then upgrade to Layer 3 routing anytime by simply re-configuring the ports. You can flexibly segment the network into domains and sub-domains, using (1) subnet IDs and user IP numbers to route traffic, and (2) custom filters based on users' physical MAC addresses to filter extraneous traffic. At Layer 2, the switch uses auto-learned and user-defined MAC addresses to discard and forward packets. At Layer 3, it looks at the user-specified routing table to route packets to their destinations.

### **VLANs for Enhanced Security & Performance**

The DGS-3312SR supports 802.1Q and port-based VLANs to improve security and bandwidth utilization. This limits the broadcast domains and confines intra-group traffic within their segments. The switch also supports GVRP (GARP VLAN Registration Protocol) for automatic VLAN configuration distribution.

### **Advanced Network Access Management**

802.1x features enable user authentication for each network access attempt. Port security features allow you to limit the number of MAC addresses per port in order to control the number of stations for each port. Static MAC addresses can be defined for each port to ensure only registered machines are allowed to access. By enabling both of these features, you can establish an access mechanism based on user and machine identities, as well as control the number of access stations.

### **Multi-Layer Access Control List (ACL)**

Access Control Lists (ACL) allow the network administrator to define policies on network traffic control. The switch supports comprehensive and multi-layer ACLs, providing a powerful tool for network management. For example, the switch can be set to block malicious bulk traffic from specific clients based either on MAC or IP addresses. Or during a virus attack, the switch can be set to restrict its flooding based on a virus's unique pattern based on TCP/UDP port number.

### **Advanced CoS Support**

The switch supports not only Layer 2 802.1p Priority Queue control, but also a variety of ways to prioritize network packets. Multi-layer information from L2 to L4 can be used to classify packet priorities. This function allows you to attach IP telephony devices or video servers to the switch to run delay-sensitive applications like video conference. The DGS-3312SR supports up to 8 CoS (Class of Service) queues.

### **Flexible Transmission Scheduling**

The switch supports 2 methods of packet transmission scheduling: Strict Priority Queuing and Weighted Round-Robin (WRR). You can select to use Strict Priority Queuing to strictly enforce your priority queues, or WRR to address bandwidth limitations at peak time. WRR allows each queue to be assigned a different percentage of the output port's bandwidth, so that lower-priority queues are not denied access to buffer space and port bandwidth.

### **IGMP Snooping for Broadcast Control**

The switch listens to IGMP (Internet Group Management Protocol) messages to build mapping table and associate forwarding filters. It dynamically configures the switch ports to forward IP multicast traffic only to those ports associated with multicast hosts.

### **Broadcast Storm Control**

To prevent too many broadcast/multicast from flooding the network, broadcast/multicast storm control is configured to screen excessive traffic. Threshold values are available to control the rate limit for each port. Packets are discarded if the respective count exceeds the configured upper threshold in a given time interval. The possible range of upper threshold is from 0 to 255k packets per second.

### **Port Mirroring**

This function allows you to mirror adjacent ports for the purpose of analyzing incoming and outgoing packets where packet patterns can be studied.

### **Spanning Tree for Redundant Backup Bridge Path**

For mission critical environments with multiple switches supporting STP, you can configure the stack with a redundant backup bridge path, so transmission and reception of packets can be guaranteed in event of any fail-over switch on the network. The

## Features

- 4 built-in 10/100/1000BASE-T ports
- 4 built-in combo SFP (mini GBIC) \*
- 2 expansion slots for Gigabit port module installation
- Selection of 4-port 1000BASE-T and SFP modules for expansion slots
- Redundant power supply support
- Jumbo frame support (up to 9,216 bytes)
- IP routing supporting RIP-1, RIP-2, OSPF routing protocols, DVMRP, PIM Dense mode
- 802.1Q VLAN, GARP/GVRP support
- IGMP snooping, 802.1p Priority Queues, port mirroring support
- Multi-layer (Layer 2 to Layer 4) ACL and CoS support
- Broadcast storm control

- 802.1D compatible, 802.1w Rapid Spanning Tree for redundant backup bridge paths
- SNMP v.1, v3 network management, 4 groups of RMON
- 802.1x port-based/MAC-based access control
- Per-port bandwidth control
- 802.3ad LACP port trunks
- Command Line Interface, TFTP firmware upgrade, Web-based management, Web GUI Traffic Monitoring support
- SNMP management/MIB support

\* Use of the SFP will disable their corresponding built-in 10/100/1000BASE-T connections.

# DES-3312SR

## Technical Specifications

## Gigabit L3 Switch

### Hardware

#### Device Ports

- 4 built-in 10/100/1000BASE-T ports
- 4 built-in combo SFP (mini GBIC) \*
- RS-232 console port

\* Use of the SFP will disable their corresponding built-in 10/100/1000BASE-T connections. These Gigabit ports can be configured for server/backbone attachments, or for switch stacking.

#### Number of Expansion Slots

2

#### Port Modules (for expansion slots)

- DEM-340MG: 4 SFP slots
- DEM-340T: 4 10/100/1000BASE-T ports

#### Port Standard/Function Support

- IEEE 802.3 10BASE-T/802.3u 100BASE-TX/802.3ab 1000BASE-T
- ANSI/IEEE 802.3 NWay auto-negotiation
- IEEE 802.3x Flow Control
- Auto MDI/MDIX
- Port mirroring

#### SFP (Mini GBIC) Support

- IEEE 802.3z 1000BASE-LX (DEM-310GT transceiver)
- IEEE 802.3z 1000BASE-SX (DEM-311GT transceiver)
- IEEE 802.3z 1000BASE-LH (DEM-314GT transceiver)
- IEEE 802.3z 1000BASE-ZX (DEM-315GT transceiver)

#### Forwarding Rate

17.8Mpps (max.)

#### Switch Fabric

24Gbps

#### Diagnostic LEDs

##### Per device:

- Power
- Console
- RPS

##### Per RJ-45 port:

- Speed
- Link/Act

##### Per SFP port:

- Link/Act

### Software

#### IP Routing

- IP v4 support
- IP Fragmentation support
- Routing protocols supported:
  - Static routing
  - RIP-1, RIP-2
  - OSPF v.2

#### VLAN

- IEEE 802.1Q Tagged VLAN
- Port-based VLAN (non-overlapping)
- GARP/GVRP
- Maximum number of VLANs: 4K

#### Priority Queues (CoS)

- Standard: IEEE 802.1p
- Number of queues: 8 per port

#### Traffic Classification (CoS)

##### Can be based on user-definable application types:

- TOS
- Diffserv (DSCP)
- Port-based
- MAC address
- IP address
- TCP/UDP port number

#### Network Access Security

- 802.1x user authentication: port-based and MAC-based
- RADIUS client for 802.1x support
- SSH2 \*
- SSL \*
- TACACS/TACACS+/XTACACS \*
- Cisco-like port security
- Multi-layer Access Control List (ACL) based on:
  - MAC
  - VLAN

802.1p

Diffserv (DSCP)

IP address

Protocol type

TCP/UDP destination port number

\* Functions available in next firmware upgrade

#### Spanning Tree

- 802.1D compatible
- 802.1w Rapid Spanning Tree

#### Multicast

- IGMP v2
- IGMP Snooping
- DVMRP
- PIM-DM

#### Port Trunk

- Number of ports per trunk: 8 (max.)
- Number of trunk per switch: 6 (max.) (in DGS-3312SR stand-alone mode only)
- Trunking mode: static
- Operation mode: load sharing
- 802.3ad LACP support

### Performance

#### Transmission Method

Store-and-forward

#### MAC Address Table

16K entries per device

#### Routing Table

2K entries per device

#### MAC Address Learning

- Dynamic entries: automatic update
- Static entries: user-defined

#### Layer 2 Packet Filtering/Forwarding Rates (half duplex)

1,488,100 pps per port (max.)

#### RAM Buffer

1MB per device

#### Jumbo Frame Size

Up to 9,216bytes

#### Broadcast Storm Control

Rate control of Broadcast, unknown Multicast and Unicast packets

### Configuration & Management

#### Management Support

- SNMP v.1, v.3
- Web-based management
- CLI (command line interface)
- RMON monitoring
- Telnet server
- Telnet remote control console
- SYSLOG
- Web GUI traffic monitoring
- Password enable
- Web MAC address browsing
- SNMP trap on MAC notification
- SNTF
- IP filtering on management interface

#### MIBs

- MIB-II (RFC 1213)
- Bridge MIB (RFC 1493)
- RMON MIB (RFC 1757)
- RIP (RFC 1724)
- OSPF (RFC 1850)
- CIDR (RFC 2096)
- 802.1Q VLAN/802.1p MIB (RFC 2674)
- IGMP MIB (RFC 2933)
- IF (Interface) MIB (RFC 2233)
- Ethernet-like MIB (RFC 1643)
- D-Link enterprise MIB

# DGS-3312SR

## Technical Specifications

## Gigabit L3 Switch

### RMON Groups

1, 2, 3, 9 (Alarm, Statistics, History, Event)

### IP Number Self-identification

Through DHCP client, Bootp client

### Firmware Upgrade

TFTP client

### Console Port

DB-9 RS-232 DCE

## Physical & Environmental

### Power Input

100 to 120 VAC, 50/60 Hz or 200 to 240 VAC, 50/60 Hz  
Internal universal power supply

### Redundant Power Backup Support

Connector to connect to external redundant power supply

### Power Consumption

30 watts (max.) (without expansion modules)

### Ventilation

60 x 60 mm DC fans x 1

### Operating Temperature

0° to 40° C

### Storage Temperature

-25° to 55° C

### Humidity

10% to 95% non-condensing

### Dimensions

440 (W) x 309 (D) x 44 mm (H) (device only)  
19-inch rack-mount width, 1 U height

### Weight

4.4 kg (device only, without expansion modules)

### Emission (EMI)

- FCC Class A  
- CE Class A  
- C-Tick

### Safety

CSA International



ACN 052 202 838

## Ordering Information

### Modular L3 Gigabit Switch

**DGS-3312SR** 4 10/100/1000BASE-T ports,  
4 combo SFP (mini GBIC), 2 expansion slots,  
redundant power support

### Optional Expansion Module

**DEM-340MG** 4 SFP GBIC slots  
**DEM-340T** 4 10/100/1000BASE-T ports

### Optional SFP Transceiver

**DEM-310GT** SFP transceiver for 1000BASE-LX, single-mode  
fiber, max. distance 10km, 3.3V  
**DEM-311GT** SFP transceiver for 1000BASE-SX, multi-mode  
fiber, max. distance 550m, 3.3V  
**DEM-314GT** SFP transceiver for 1000BASE-LHX, single-mode  
fiber, max. distance 40km, 3.3V  
**DEM-315GT** SFP transceiver for 1000BASE-ZX, single-mode  
fiber, max. distance 80km, 3.3V

### Optional Redundant Power Supply

**DPS-200** 60 watts redundant power supply  
**DPS-800** 2-slot redundant power supply chassis  
**DPS-900** 8-slot redundant power supply chassis



Specifications subject to change without prior notice.  
D-Link is a registered trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

<b>U.S.A</b>	TEL: 1-714-885-6000	FAX: 1-866-743-4905
<b>Canada</b>	TEL: 1-905-8295033	FAX: 1-905-8295223
<b>Europe</b>	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
<b>Germany</b>	TEL: 49-6196-77990	FAX: 49-6196-7799300
<b>France</b>	TEL: 33-1-30238688	FAX: 33-1-30238689
<b>Benelux</b>	TEL: 31-10-282-1445	FAX: 31-10-282-1331
<b>Italy</b>	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
<b>Iberia</b>	TEL: 34-93-4090770	FAX: 34-93-4910795
<b>Sweden</b>	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
<b>Norway</b>	TEL: 47-22-309075	FAX: 47-22-309085
<b>Denmark</b>	TEL: 45-43-969040	FAX: 45-43-424347
<b>Finland</b>	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
<b>Singapore</b>	TEL: 65-6774-6233	FAX: 65-6774-6322
<b>Australia</b>	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
<b>Japan</b>	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
<b>China</b>	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
<b>India</b>	TEL: 91-022-652-6696	FAX: 91-022-652-8914
<b>Middle East (Dubai)</b>	TEL: 9714-8834234	FAX: 9714-8834394
<b>Turkey</b>	TEL: 90-212-335-2553	FAX: 90-212-335-2500
<b>Egypt</b>	TEL: 202-414-4295	FAX: 202-415-6704
<b>Israel</b>	TEL: 972-9-9715700	FAX: 972-9-9715601
<b>Chile</b>	TEL: 56-2-232-3185	FAX: 56-2-232-0923
<b>Brasil</b>	TEL: 55-11-55039320	FAX: 55-11-55039321
<b>South Africa</b>	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
<b>Russia</b>	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
<b>Taiwan</b>	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
<b>D-Link Corp.</b>	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE  
Rev. 01 (Dec. 2003)