D-Link®

Share your printers



3-PORT PRINT SERVER

D-Link

18

2 💍

SHARE UP TO 3 DEVICES

Share up to 3 printers/multifunction equipment

with a single print server

FOR BUSINESS USE

For environments that deploy multiple printers/multifunction

equipment within a close proximity

SUPPORTS MULTIFUNCTION EQUIPMENT

Compatible with scanning and fax functions of multifunction equipment

DPR-1061



SHARE YOUR PRINTERS AND MULTIFUNCTION EQUIPMENT

The DPR-1061 3-Port Print Server provides users with 3 available ports from a single device, and offers print and scan compatibility for those who are using multifunction equipment. This print server allows users to directly send out documents from their PC for fax transmissions. Enjoy sharing your printer and multifunction equipment's printing, faxing, and scanning abilities among the users on your network - all with a single print server.

SIMULTANEOUS OPERATION OF ALL DEVICES

Equipped with a powerful CPU, large memory, high speed USB ports and network data transfer, this print server makes your operations fast. Devices attached to the DPR-1061 can print, scan, and fax at the same time, giving this multi-port print server a similar performance to 3 separate single-port print servers at a fraction of the cost.

ACCESS SECURITY AND MULTIPLE OS SUPPORT

The DPR-1061 provides the necessary security by allowing the administrator to configure user access right to the network printers and equipment. It supports a wide range of network OS including: Windows 95/98/ME/NT 4.0/2000/XP, Apple MacOS with AppleTalk, Linux, Solaris, SCO Unix, IBM AIX and NetWare 5.x native NDS. Enjoy the flexibility and compatibility in major network OS that this print server has to offer.

REMOTE PRINTING SUPPORT

The DPR-1061 supports the Internet Printing Protocol (IPP), enabling remote users to output files to their office printer even when they are away from the site. HP PJL protocol is also supported for bi-directional network printer communication, providing network administrators with critical information about the network printer. Regardless of where you are, never worry about being unable to print out important files ever again with this print server's convenient functions.



D-Link

DPR-1061 SHARE YOUR MULTIFUNCTION EQUIPMENT

DPR-1061

WHAT THIS PRODUCT DOES

The DPR-1061 3-Port Print Server is a versatile multi-port print server ideal for use at the office, school or business. With 2 USB ports and 1 parallel port for printer connection, this device gives you the versatility of adding multiple printers or multifunction equipment to your network. Supporting scan, fax, and print functions, the DPR-1061 can create up to 3 printer/multifunction equipment connections, providing an easy and cost-effective way for you to share your multiple devices over a network.

FEATURES

- + 2 USB 2.0 printer ports
- + 1 parallel printer port
- + 1 10/100BASE-TX Ethernet port
- + Supports Internet Printing Protocol (IPP) for remote printing
- + Supports a wide range of printers including GD
- + Supports scan and fax functions of multifunction equipment
- + Supports TCP/IP, NetBEUI Operating Systems (Windows, Linux, Unix, and Mac OS)

YOUR NETWORK SETUP

Internet Cable/DSL Modem Wired Boute Desktop PC **DPR-1061** Print Serve Centronic Printer Cable USB USB Multifunction Equipment

Central Driver Languages Supported				
			*	
				╬═
		-	0	

F FC D-Link Cornoration No. 289 Xinhu 3rd Road, Neihu, Taipei 114, Taiwan Specifications subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners.

. Release 02 (Mav. 2008)

TECHNICAL SPECIFICATIONS

HUMIDITY

5% to 95% non-condensing DIMENSIONS 7.58 x 4.66 x 1.22 inches (192.5 x 118.4 x 31 mm)

WEIGHT

292a (10.3 oz)

CERTIFICATIONS

FCC CE C-Tick IC CSA

PRINTER COMPATIBILITY LIST

- + AVISION: MF3100L
- + BENO: CM3000
- + BROTHER: MFC-210C, MFC-420CN, MFC-3240C, MFC-7220
- CANON: PIXMA MP110, PIXMA MP150, PIXMA MP160, PIXMA MP170, PIXMA MP180, PIXMA MP450, PIXMA MP460, PIXMA MP500, PIXMA MP510, PIXMA MP600, PIXMA MP810, PIXMA MP830, PIXMA MP950, PIXMA MP960
- DELL: PHOTO 966
- EPSON: PM-A970, PM-A920, PM-A820, PM-A720, PM-A950, PM-A890, PM-A750, PM-A650, STYLUS CX2900, STYLUS CX3700, STYLUS CX3900, STYLUS CX4100, STYLUS CX4700, STYLUS + CX4900, STYLUS CX5700F, STYLUS CX5900, STYLUS CX6900F STYLUS PHOTO RX530, STYLUS PHOTO RX580, STYLUS PHOTO RX590, STYLUS PHOTO RX630, STYLUS PHOTO RX650
- FUJI XEROX: WORKCENTRE 3119
- HP: DESKJET F380, PSC1315, PHOTOSMART C1350, PHOTOSMART C1610, PHOTOSMART C3180, PHOTOSMART C4180, PHOTOSMART C5180, OFFICEJET 4255, OFFICEJET 4355, OFFICEJET 5510, OFFICEJET 5610, OFFICEJET 6110, OFFICEJET 7210, LASERJET 3050
- LEXMARK: X3470, X5470
- + SAMSUNG: SCX-4100, SCX-4200

PRINT SERVER

Power 4 + Ethernet Link Activity

Printer (1 to 3) +

DIAGNOSTIC LEDS

STANDARDS

+ IEEE 802.3

IEEE 802.3n

+ 2 USB 2.0 ports

browsers

+ 1 Parallel Printer port

DEVICE MANAGEMENT

DHCP server and client

+ 1 10/100BASE-TX Ethernet LAN port

Through Internet Explorer v6 or later; or other Java-enabled

Print Server Administration program running under Windows

IEEE 1284

USB 2.0

PORTS

+

+

POWER INPUT

5.0V DC/2.5A (Through external power adapter)

OPERATING TEMPERATURE 0° to 50°C (32° to 122°F)

STORAGE TEMPERATURE

-25° to 55°C (-13° to 131°F)

OS SUPPORT

- Windows Vista/XP/2000/NT4/ME/98SE/95
- + Apple Mac OS 9.x to MAC OS X 10.4.x
- Linux +
- UNIX lpr/lpd (HP-UX, SunOS, Solaris, SCO, UnixWare, IBM AIX)
- NetWare 5.x NDPS LPR Remote Printing