




— DWL-2000AP+

AirPlus G+



802.11g High-Speed Wireless Access Point

Real Throughput 10X Faster

The AirPlusG+™ DWL-2000AP+ is an enhanced high-performance 802.11g wireless Access Point for use indoors. This device supports wireless networking speeds of up to 54Mbps, while providing seamless interoperability with all existing 802.11b and 802.11b+ wireless equipment. With high data transfer rates, better security and built-in bridge function, this device is the ideal wireless solution that offers an upgrade to a fast, new technology while protecting your past investments through interoperability with your current network equipment.

Up to 54Mbps Speed on 2.4GHz Frequency Band

Providing transmission speeds of up to 54Mbps, the DWL-2000AP+ compares favorably with 802.11b devices that offer 11Mbps speed, and with 802.11b+ equipment that gives 22Mbps transmission. This enhanced speed and adoption of 2.4GHz frequency, now available for public use in most countries, plus the mobility and convenience inherent in a wireless LAN, make this device an ideal solution for bandwidth intensive WLAN applications.

Real Throughput 10 Times Faster Than 802.11b Wireless LAN

Apart from the higher theoretical network data transfer speed of 54Mbps for 802.11g against the 11Mbps for 802.11b, the DWL-2000AP+ also delivers a much faster data transmission than other wireless LAN devices. In a typical working environment with multiple users accessing the network at the same time, the DWL-2000AP+ operates at 10 times the speed of the normal 802.11b wireless LAN equipment, which is made possible by means of a turbo engine firmware inside this AP.

Compatible With 802.11b and 802.11b+

802.11g's compatibility with existing wireless LAN standards means that you do not need to change your entire network to maintain connectivity. The DWL-2000AP+ can transmit data at up to 54Mbps when used with D-Link AirPlusXtremeG+™ and other 802.11g products.

Built-in Bridge Functions

The DWL-2000AP+ can be configured to operate in any one of the 4 modes: (1) as a wireless access point (AP), (2) a point to point wireless bridge, (3) a point to multi point wireless bridge, or (4) a wireless client. With these built-in functions, the DWL-2000AP+ gives you the flexibility to configure the device to meet your environment's requirements.

Easy Migration to Higher Bandwidth

By maintaining compatibility with your existing wireless network equipment, the DWL-2000AP+ lets you upgrade to a higher speed at the pace you want. The DWL-2000AP+ and other 802.11g standard devices can be gradually added to your network, while the rest of your older network remains perfectly connected.

Embedded DHCP Server

The DWL-2000AP+ includes an embedded DHCP server that, once enabled, will automatically assign IP addresses to wireless clients. This unique feature makes the DWL-2000AP+ an ideal solution for quickly creating and extending a wireless local area network (WLAN) in offices or other workplaces, and at trade shows and other special events.

Key Features

- 802.11g wireless LAN standard
- Up to 54Mbps data rate *
- Real throughput 10x faster than 802.11b devices **
- Compatible with 802.11b/b+ standards
- Dynamic data rate scaling at 1, 2, 5.5, 6, 9, 11, 12, 18, 22, 24, 36, 48, and 54Mbps
- Maximum reliability, throughput and connectivity with automatic data rate switching
- Stronger user-selectable 64 /128/256-bit WEP data encryption
- 4 operation modes: access point, point to point wireless bridge, point to multipoint wireless bridge, wireless client
- 10/100BASE-TX LAN port with auto MDI/MDIX
- DHCP client/server
- Web-based configuration
- Management utility supports Windows 98 SE, 2000, XP, ME

* When used with other 802.11g devices

** When used with other AirPlusG+™ devices

DWL-2000AP+

Technical Specifications

2.4GHz Wireless LAN

Hardware

Wireless LAN Standards

- 802.11b
- 802.11b+
- 802.11g

Data Rates

- 802.11g: up to 54Mbps (6/9/12/18/24/36/48/54Mbps)
- 802.11b+: up to 22Mbps
- 802.11b: up to 11Mbps (1/2/5.5/11Mbps)

Transmission Technology

DSSS

RF Frequency Range

2.4 to 2.4835GHz

Frequency Stability

Within +/- 25ppm

Operating Channels

- 1 to 11 channels (North America)
- 1 to 13 channels (Europe)

Data Modulation Type

DBPSK, DQPSK, CCK, PBCC and OFDM (BPSK/QPSK/16-QAM/ 64-QAM)

Antennas

- 1 external dipole antenna, 2dBi Gain
- 1 internal embedded antenna

Transmit Output Power

- 802.11b: 16dBm (typical)
- 802.11g: 14dBm (typical)

Receive Sensitivity (for 802.11b)

- (typically @PER < 8% packet size 1024 @ 25 °C +/- 5 °C)
- 22Mbps (PBCC): -80dBm
- 11Mbps (PBCC): -85dBm
- 11Mbps (CCK): -84 dBm
- 5.5Mbps (CCK): -87 dBm
- 2Mbps (QPSK): -90 dBm
- 1Mbps (BPSK): -92 dBm

Receive Sensitivity (for 802.11g)

- (typically @PER < 8% packet size 1024 @ 25 °C +/- 5 °C)
- 54Mbps (OFDM): -71 dBm
- 48Mbps (OFDM): -72 dBm
- 36Mbps (OFDM): -77 dBm
- 24Mbps (OFDM): -80 dBm
- 12Mbps (OFDM): -86 dBm
- 9Mbps (OFDM): -87 dBm
- 6Mbps (OFDM): -89 dBm

Operating Range *

- Indoors: 100 meters (328 feet)
- Outdoors: 400 meters (1,312 feet)

* Environmental factors may adversely affect range

Ethernet Interface

10/100BASE-TX port with auto MDI/MDIX support

Diagnostic LEDs

- Power
- LAN
- WLAN

Software Features

Operating Modes

- Standard Access Point
- AP Client
- Bridge: Point-to-Point, Point-to-Multi Point

Security

- WEP user-selectable 64/128/256-bit data encryption
- Password protect
- 802.1x security (MD5 and TLS)
- MAC filtering
- SSID broadcast disable
- Wi-Fi™ Protected Access

Configuration & Management

- DHCP client/server
- Management Utility supports Windows 98SE, ME, 2000, XP
- Status log

Configuration Reset

Default reset button

Physical & Environmental

Power Supply

- 5 VDC +/- 5%, 2.5A
- Through external power adapter

Dimensions

142 x 109 x 31 mm (device only)

Weight

243 grams (device only)

Operating Temperature

0 ° to 55 °C

Storage Temperature

-20° to 65 °C

Humidity

5% to 95% non-condensing

Regulation Compliance

- US: FCC Part 15 Class B
- Europe: CE/R&TTE

Box Includes

- DWL-2000AP+ wireless LAN AP
- CD (includes AP Manager software, user's manual, Quick Installation Guide, Acrobat Reader 5.0)
- Quick Installation Guide (printed)
- 1.8 m Ethernet cable
- External power adapter
- Mounting kit
- Rubber feet



Ordering Information

DWL-2000AP+

802.11g Wireless LAN Access Point

Please specify your model number as follows:

DWL-2000AP+/ANA

US power adapter, North America frequency

DWL-2000AP+/EEU

EU power adapter, EU frequency

DWL-2000AP+/ENA

EU power adapter, North America frequency

DWL-2000AP+/BEU

UK power adapter, EU frequency

DWL-2000AP+/NEU

Australia power adapter, EU frequency

DWL-2000AP+/CN

For use in China

TDWL-2000AP+

For use in Taiwan

D-Link®

Specifications subject to change without prior notice.
D-Link and AirPlusG+ are registered trademarks and AirPlusG+ is a trademark of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-714-885-6000	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-22-309075	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
Japan	TEL: 81-3-5434-9678	FAX: 81-3-5434-9868
China	TEL: 86-10-8518-2533	FAX: 86-10-8518-2250
India	TEL: 91-022-652-6696	FAX: 91-022-652-8914
Middle East (Dubai)	TEL: 9714-8834234	FAX: 9714-8834394
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Latinamerica	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-55039320	FAX: 55-11-55039321
South Africa	TEL: 27(0)1266-52165	FAX: 27(0)1266-52186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299



RECYCLABLE
Rev. 03 (Jun. 2004)