

How to configure in router mode?

- 1) Find a nearby outlet to an Internet-ready device (eg., a modem or router).
- 2) Then move the switch to "RT mode" and plug the GO-RTW-N300 into the wall outlet. Verify that the power LED has changed to blue.



- 3) Connect one end of the ethernet cable to the internet ready device (eg., a modem or router), and then plug the other end into the INTERNET port of the GO-RTW-N300.
- 4) Plug another ethernet cable the LAN port of the GORTW-N300 and the other of the cable into the port on PC, or you can connect to the router wirelessly.



5) From the computer connected to the GO-RTW-N300, open a web browser and go to http://192.168.0.1/

On the login screen, type admin as the user name and leave the password blank.

How to configure in router mode?



Product Page: GO-RTW-N300	Hardware version: A1 Firmware Version: 1.00
D 74-1-1	
D-Link	
Client Router	Internet
DEBK	
	<u> </u>
Lan IP 192.168.0.1 Internet IP 192	.168.1.116 DHCP
Wan Setup	
Connect type: DHCP 💌	
Wireless Setup	
SSID: GO-RTW-N300	
Key:	(8-63 characters or 64 hex digits)
Save and Cor	nect Advanced Network Settings
6) In the Wan Setup option, you	Wan Setun
must select the type of Internet	Hansetap
connection provided by your in-	Connect type: DHCP DHCP
ternet service provider (ISP).	DHCP

 In Wireless Setup, you can set the name of your wireless network (SSID). By default, the wireless network is configured with the name "Go-RTW-N300" and no password, so you can set a WPA key.

Wireless Setup		
SSID: Key:	GO-RTW-N300	(8-63 characters or 64 hex digits)



8) Once configured save changes from the Save and Connect button to finish setting.

